

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

| | | | | | |
|---|---|--|----------------------------------|---|--|
| 1. AGENCY USE ONLY (Leave blank) | | 2. REPORT DATE 10 Oct 97 | | 3. REPORT TYPE AND DATES COVERED Final (8 July 97 - 10 Oct 97) | |
| 4. TITLE AND SUBTITLE Combat Service Support (CSS) Vector-in-Commander (VIC) Analysis in Support of Force XXI Analyses Division Design Analysis -- Phase III CSS Analysis of VIC Dynamic Gaming Conservative Heavy Division Interim Design (North East Asia 2.0) | | | | 5. FUNDING NUMBERS | |
| 6. AUTHOR(S) Peter Barnes, John Steffey | | | | | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army TRADOC Analysis Center - Fort Lee ATTN: ATRC-L Fort Lee, VA 23801-1511 | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER Technical Report TRAC TR 1092 | |
| 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) HQ TRAC Fort Leavenworth, KS 66027-2345 | | | | 10. SPONSORING / MONITORING AGENCY REPORT NUMBER | |
| 11. SUPPLEMENTARY NOTES Provided supporting documentation for the Force XXI Division Design Analysis Phase III Division Combat Service Support Analysis. | | | | | |
| 12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution is unlimited; approved for public release. | | | | 12b. DISTRIBUTION CODE | |
| 13. ABSTRACT (Maximum 200 words) In 1995, TRADOC initiated the analytical process described in the March 1995 draft Joint Venture (JV) Campaign Plan. The resulting analyses provide the basis for redesigning today's Warfighting Army for the 21st century. The combat unit elements, combat service elements, and the combat service support elements needed to be analyzed individually to determine whether or not each of these sections would be able to effectively perform under the given scenario conditions. TRAC-Lee was tasked to analyze the CSS capabilities of the three (3) division designs (Conservative Heavy, Strike, Brigadist) for DDA Phase III. The three division designs were dynamically gamed using the Vector-in-Commander model in the LANTICA III, Northeast Asia 2.0, and Southwest Asia 4.2 scenarios. The CSS elements represented in VIC were analyzed by TRAC-Lee with the primary focus of the analysis was on the maintenance and supply operations and how the CSS units functioned for the given scenario. This analysis concluded that the CSS structure in the Conservative Heavy Division can support the division during a 60-hour battle such as the one portrayed in Northeast Asia 2.0. There were a few problem areas in the CSS elements that were focused on in this analysis. Some of the artillery units used all of their ammunition reserves and were not resupplied in a timely manner due in part by the lack of ammunition transporters available. | | | | | |
| DTIC QUALITY INSPECTED 2 | | | | | |
| 14. SUBJECT TERMS Maintenance Analysis, Supply Analysis | | | | 15. NUMBER OF PAGES 47 | |
| | | | | 16. PRICE CODE | |
| 17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED | 18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED | 19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED | 20. LIMITATION OF ABSTRACT UL | | |

19980113 214

GIST

STUDY TITLE: Combat Service Support (CSS) Vector-in-Commander (VIC) Analysis in Support of Force XXI Analyses Division Design Analysis – Phase III CSS Analysis of VIC Dynamic Gaming Conservative Heavy Division Interim Design (North East Asia 2.0)

PURPOSE: The purpose of this analysis was to produce quantitative analysis of the Conservative Heavy Division Interim Design's combat service support (CSS) structure which was dynamically gamed in the North East Asia 2.0 scenario with the VIC model. The focus of the analysis was on the maintenance and supply operations and how the CSS units functioned for the given scenario.

MAIN ASSUMPTIONS: The principal assumptions of this study include: (a) all repair parts were available upon request, (b) Echelons-Above-Division (EAD) were fully resourced, and (c) CSS enablers and other technological equipment are present.

PRINCIPAL FINDINGS: The CSS structure in the Conservative Heavy Division could support the division during the 60-hour battle in the NEA 2.0 scenario with one exception. Several artillery units expended all of their ammunition resources at some time during the scenario and could not be resupplied in a timely manner.

IMPACT: This report suggests that the CSS structure in the Conservative Heavy Division is sufficient to sustain the division in a scenario such as the one portrayed in NEA 2.0.

STUDY DIRECTORS AND STUDY AGENCY: Peter Barnes, TRADOC Analysis Center, Ft Lee, VA (DSN 539-1809, COM 804-765-1809, FAX 804-765-1456), John Steffey, TRADOC Analysis Center, Ft Lee, VA (DSN 539-1831, COM 804-765-1831, FAX 804-765-1456).

STUDY SPONSOR AND SPONSOR POC: TRADOC Analysis Center, Antoniette McGrady, DSN 539-1826, COM 804-765-1826.

DTIC:

SECURITY CHECKLIST

1. TITLE OF STUDY: Combat Service Support (CSS) Vector-in-Commander (VIC) Analysis in Support of Force XXI Analyses Division Design Analysis – Phase III CSS Analysis of VIC Dynamic Gaming Conservative Heavy Division Interim Design (North East Asia 2.0)

2. CLASSIFICATION ASSIGNED (CHECK ONE)

☐ TS ☐ SECRET ☐ CONFIDENTIAL ☒ UNCLASSIFIED

A. ☐ ORIGINAL CLASSIFICATION. IF XGDS, IDENTIFY APPROVING TOP SECRET AUTHORITY

B. ☐ CONTINUING CLASSIFICATION. CLASSIFICATION BASED ON THE FOLLOWING DESCRIBED SOURCE DOCUMENTS OR CLASSIFICATION GUIDE:

(1) _____

(2) _____

C. ☐ DOWNGRADING/DECLASSIFICATION INSTRUCTION APPLIED

D. ☐ BASIS FOR DOWNGRADING/DECLASSIFICATION INSTRUCTIONS INDICATED IN PARA 2C ABOVE.

3. THIS STUDY CONTAINS NOFORN OR NON-TRADOC INFORMATION. NO

A. RESTRICTED DATA OR FORMERLY RESTRICTED DATA. NO

B. INFORMATION ORIGINATED BY OTHER DOD AGENCIES. YES

C. INFORMATION ORIGINATED BY AGENCIES OUTSIDE OF DOD. NO

D. SPECIAL CATEGORY INFORMATION. (IF YES, IDENTIFY, I.E., CRYPTO, NATO) NO

E. INTELLIGENCE INFORMATION. NO

4. RELEASE TO FOREIGN NATIONALS OF INFORMATION IDENTIFIED IN PARA 3 ABOVE HAS BEEN COORDINATED WITH, OR APPROVED IN ADVANCE BY: NONE

5. UNLIMITED DISTRIBUTION; APPROVED FOR PUBLIC RELEASE PER DIRECTOR, TRADOC ANALYSIS CENTER, FORT LEE, (TRAC-LEE).

Combat Service Support (CSS) Vector-in-Commander
(VIC) Analysis in Support of Force XXI Analyses
Division Design Analysis -- Phase III CSS Analysis of VIC
Dynamic Gaming Conservative Heavy Division Interim
Design (North East Asia 2.0).

Technical Report



Prepared by:

Peter Barnes
PETER BARNES
ORA, TRAC-LEE
John Steffey
JOHN STEFFEY
ORA, TRAC-LEE

Certified by:

Gerald A. Klopp
GERALD A. KLOPP
Director, TRAC-LEE

Combat Service Support (CSS)
Vector-in-Commander (VIC) Analysis
in Support of Force XXI Analyses

Division Design Analysis -- Phase III
CSS Analysis of VIC Dynamic Gaming
Conservative Heavy Interim Design (Northeast Asia 2.0)
08Jul97 VIC Analysis Data

1. General.

a. The Commanding General (CG) Training and Doctrine Command (TRADOC) tasked the TRADOC Analysis Center (TRAC) to conduct an analysis of the Combat Service Support (CSS) Division redesign concept. TRAC at Fort Lee, Virginia (TRAC-LEE) used Vector-in-Commander (VIC) analysis to provide quantitative analysis of that concept.

b. The dynamic gaming with the VIC model is based on the Northeast Asia 2.0 scenario with a total duration of 60 hours incremented in four hour time periods (TP) and a four (4) hour reorder cycle time between CSS units. The modeled force, the Conservative Heavy Interim Division, consists of three brigades with corps support. Specific descriptions and details for both the scenario and modeled force are provided in the main report.

c. The analysis focuses first on those key maneuver unit resources necessary for a unit to perform its designated mission. The specific resources addressed are weapon system availability and the timely availability of supplies. Secondly, various aspects of the CSS system are examined to isolate bottlenecks or shortages which limit the provision of needed services. And conversely, excesses or under-utilized CSS resources are identified for this scenario.

d. The analysis entails two major areas: maintenance support and supply support. Since the medical support system for the treatment of personnel is very similar in function to that of the maintenance system, medical support is addressed along with maintenance.

e. VIC unit name designators are used in this report for brevity. Appendix A shows the cross reference between actual unit names and VIC unit names.

2. Model Description.

a. The Vector-in-Commander (VIC) model is a two-sided, deterministic simulation of integrated land and air combat. The level of resolution is the maneuver battalion. As a deterministic model, VIC relies upon expected values; weapon systems, transporters, inventories/stockage levels, and consumption can be fractional values. VIC is event stepped for maneuver elements and both time stepped and event stepped for calculation of combat service support (CSS) effects. The combat and combat support (CS) functions in VIC produce a workload for the CSS system. Two key modules within VIC are used to represent the CSS system: Return to Duty (RD - maintenance) and Logistics (LO - supply).

b. The return-to-duty (RD) module operates on equipment and noncrew personnel, both of which are referred to as systems, as well as crews for key combat vehicles.

(1) Workloads. The attrition modules generate combat casualty workload in the form of combat-damaged systems. These quantities are adjusted to factor out catastrophic damage/killed in action (KIA) and abandonments (equipment only) before becoming a workload on the RD system. Reliability failures to equipment and disease and nonbattle injury (DNBI) to personnel are also generated, resulting in their removal from units and their introduction as workload upon the RD system.

(2) Processes. The RD module contains representations of the recovery, evacuation, and repair functions.

(a) Recovery is constrained by the availability of operational recovery vehicles. Recovery operations are represented as a delay time of 57 to 96 minutes which includes round trip travel, hook-up, and drop-off. The recovery time varies from vehicle to vehicle and the primary location of that vehicle.

(b) Evacuation is constrained by the availability of operational evacuation vehicles and dynamic evacuation times that are a function of distance and time on the main supply route (MSR) network.

(c) Repair is constrained by the available strength and type of assigned mechanics or medical personnel. Of course repair throughput is impacted by the 'time to repair' but repair time is determined by design factors and not CSS. A maintenance unit's maintenance man-hours (MMH) is degraded by fifty percent when that unit has to relocate on the battlefield. This degradation is calculated to the nearest quarter of an hour; therefore, a maintenance unit's MMH during a portion of a TP could be degraded while the remaining MMH are unaffected. The degradation of MMH availability is based on the premise that a maintenance facility will have only 50 percent of its assets (to include personnel) fully functioning at any time during a battlefield relocation.

(3) Products. The final product of the RD module is the return of crewed systems to owning units. Intermediate products of the various RD processes include recovered systems, evacuated systems, and repaired systems.

(4) Combat impacts on RD processes. Impacts include attrition of RD assets, productivity degradation due to unit movement, changes in evacuation distances due to unit movements, and changes in evacuation speeds due to congestion of MSR links.

c. The logistics (LO) module provides the support structure to facilitate the resupply of ammunition, fuel, and other supplies to maneuver units and the restocking of these supplies at supply units.

(1) Workloads. The attrition modules dynamically generate the workload for ammunition as units engage in conflict. As units move and change posture they create a workload for fuel. A workload for other supplies is generated by a daily consumption rate, depending upon unit types. When maneuver units deplete their basic loads to specified reorder levels, a requirement for resupply is levied on the CSS system.

(2) Processes. The LO module contains representation of the resupply and move functions. Resupply to maneuver units is constrained by the availability of resupply vehicles, availability of supplies at supply units, load times, and travel time between the unit and its supplier. The availability of supplies at supply points is constrained by transportation, availability of load facilities, and load/unload times. The move function is constrained by the availability of CSS trucks, congestion of the MSRs, and travel times between supply units.

(3) Products. The final product for the resupply and distribution system is the replenishment of expended ammunition, fuel, and other supplies to maneuver units. Intermediate products include the restocking of resupply units and the movement of supplies along the MSRs from higher echelon supply units.

(4) Combat impacts on LO processes. Attrition and movement of supply units as a result of combat effects degrade the ability of these units to perform their resupply function. Resources which can be lost at the supply units include resupply vehicles, stocks, and materiel-handling equipment (MHE). The relocation of supply units results in degradation of their receipt/issue capability during the move. In addition,

attrition of resupply vehicles, both at the maneuver unit and along the MSRs, degrades the ability of the CSS system to deliver supplies.

3. Assumptions.

a. Maintenance characteristics and parameters of all systems remain constant across the scenario.

b. When damaged weapon systems reach a maintenance facility, the correct tools, parts, and equipment are present at the facility. If the number of mechanics necessary to work on the damaged weapon system is available, they will begin working on the damaged weapon system immediately (i.e., prep time and time spent for damage assessment are not played in the model).

c. The DNBI rate remains constant across the scenario.

d. Resupply of all stockage items is available from echelons above corps (EAC).

4. Sufficiency Criteria.

a. Equipment. Maintain 80 percent availability of systems that have not been destroyed or abandoned. Rationale: Army Regulation (AR) 220-1, Unit Readiness Reporting, defines an equipment availability status of 80-90 percent as category C2 which is fully combat ready with minor risk.

b. Personnel.

(1) Have no weapon systems in awaiting-reissue queue due to nonavailability of crews. Rationale: The availability of weapon systems crews affects the availability criterion for combat systems.

(2) Maintain 80 percent personnel strength level for all modeled personnel. Rationale: AR 200-1 defines a personnel strength level of 80-90 percent as category C2 which is combat ready with minor risk.

c. Supply. Have no zero balance of any supply-class subitem (e.g., 155mm, 120mm, POL). Rationale: The lack of a specific type could adversely affect tactical options.

5. Maintenance Analysis.

a. The six weapon system categories covered in this analysis are shown in table M-1. The Fixed Wing category was not represented in the CSS system. In addition, medical treatment of personnel and weapon system crews are presented as a separate category.

| Category | Weapon System |
|-------------|---|
| TANK | M1A2/120 |
| AFV | M2A3/TOW FSCS/45 BSFV-E M3A3/TOW |
| ADA | AVENGER |
| MLRS | MLRS_D |
| CANNON | CRUSADER-D |
| HELICOPTERS | AH64D RAH66 RAH66D |

Key Weapon Categories
Table M-1

b. The primary maintenance performance measure at the maneuver unit level is availability of unit weapon systems. Availability of unit weapon systems is determined by the current strength of weapon systems at a maneuver unit versus the initial strength less the number of catastrophically killed weapon systems at the same maneuver unit. The number of weapon systems available is a function of many dependent and interdependent factors. These factors can be partitioned into two groups: (1) those factors which render weapon systems inoperable: combat damage and reliability and (2) factors that contribute to the return of repaired systems to combat. When more weapon systems are returned to combat, a larger population is available for combat and reliability failure, which in turn workloads the Return-to-Combat (RTC) support system.

(1) Factors which cause weapon systems to become inoperable are combat damage and reliability failures. Combat damage is a function of the interaction of opposing forces resulting in catastrophic kills and repairable battle damage. The percentage of catastrophic kills versus the percentage of repairables varies by weapon system due to threat weapons and survivability characteristics. Table M-2 shows the percent repairable for each system once combat damaged. The percentages are not measures of overall survivability but are conditional results based on a weapon system first being combat damaged. Overall survivability also involves the likelihood of a weapon system being acquired and then being hit by the enemy. The percentages in table M-2 are, therefore, predicated on the occurrence of these two events.

| Category | Weapon System |
|------------|---------------|
| M1A2/120 | 93 |
| M2A3/TOW | 83 |
| FSCS/45 | 83 |
| BSFV-E | 83 |
| M3A3/TOW | 83 |
| AVENGER | 69 |
| MLRS-D | 71 |
| CRUSADER-D | 49 |
| AH64D | 41 |
| RAH66 | 41 |
| RAH66D | 41 |

Percent Repairable by Weapon System
Table M-2

(2) Permanent losses of operational systems can occur in several ways. The most frequent is usually due to catastrophic combat damage. In addition, both types of candidate repairables (combat and reliability) are subject to weapon system abandonment at the maneuver unit or maintenance unit level. Maneuver and maintenance unit abandonments of weapon systems occur due to immediate war-fight conditions, thus becoming permanent losses like catastrophic kills. Weapon systems can be traveling on an MSR when the scenario ends; thus these weapon systems are not considered part of a combat unit's arsenal. Another key factor which affects availability is the nonavailability of an owning unit. This occurs when a maintenance unit has repaired systems but does not have a maneuver unit in its area of influence with authorization to accept the system. In some cases, such weapons are never reissued during the scenario. Crewed weapon systems' RTC may be delayed because the appropriate number of crew members is not available to operate the weapon system. All six of these factors (catastrophic damage, abandonments, currently being reissued, unit non-availability, and weapon systems waiting crews) are independent of the CSS system performance. Table M-3 shows the number of systems for each of these categories at the end of the scenario.

| Weapon | # Weapons Waiting Units | # Weapons Waiting Crews | # Weapons Being Reissued | Maint Unit Aband's | Man Unit Aband's | K-Kills | Total |
|------------|----------------------------|----------------------------|-----------------------------|-----------------------|---------------------|---------|-------|
| M1A2/120 | 0.0 | 0.0 | 1.1 | 1.9 | 6.3 | 1.7 | 11.0 |
| M2A3/TOW | 0.0 | 0.0 | 0.1 | 0.0 | 6.7 | 4.7 | 11.5 |
| FSCS/45 | 0.0 | 0.0 | 0.2 | 0.6 | 4.1 | 2.3 | 7.2 |
| BSFV-E | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| M3A3/TOW | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| AVENGER | 0.0 | Not crewed | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| MLRS-D | 0.0 | 0.6 | 0.8 | 0.0 | 0.0 | 0.0 | 1.4 |
| CRUSADER-D | 0.0 | 1.2 | 2.6 | 0.0 | 0.0 | 0.3 | 4.1 |
| AH64D | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| RAH66D | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| RAH66 | 0.0 | 0.0 | 1.1 | 0.0 | 0.0 | 0.0 | 1.1 |
| Total | 0.0 | 1.8 | 5.9 | 2.5 | 17.1 | 9.0 | |

Weapon System Losses
Table M-3

(3) Reliability failures are based on mean hours between failures (MHBf) for the major subsystems of each weapon. The major subsystems for this study are Automotive, Armament, Helicopter, and Medical. Of course, the subsystems that fail or are damaged vary by weapon systems (e.g., the M1A2/120 is composed of both subsystems, automotive and armament, while only automotive is represented for the heavy equipment transporter (HET)). Each subsystem is serviced by a different mechanic type. In addition, the MHBf can vary by subsystem for each weapon. Helicopters, for this analysis, are serviced by a single type master mechanic although both automotive and armament failures occur for helicopters. In addition, all wounded/DNBI personnel are treated by a single medical type. The availability and performance of trucks used for resupply is addressed in the supply section of the report.

(4) Factors which influence the RTC of weapon systems are recovery, evacuation, and repair (to include medical treatment of personnel and crews) resources. Each of the CSS resources which performs these services is subject to both combat damage and reliability failure, which determine their availability for weapon system processing and treatment of personnel. Recovery and evacuation are performed on a designated priority basis, while repair and treatment are based on a more complex priority system. Further complicating the impact of repair on weapon system RTC are the repair characteristics of individual weapon systems. These characteristics vary by level of repair (i.e., unit (ORG), direct support (DS), general support (GS)), and mean time to repair for each type repair (combat, reliability). These characteristics represent a very complex interrelated system which determines the number of operational weapon systems.

c. Analysis. The maintenance analysis is divided into three sections (Support Services Sufficiency, Key Weapon Availability, and CSS Workloads):

(1) Support Services Sufficiency.

(a) Recovery - Weapons.

1 Recovery operations serviced the recovery workload in a timely manner. "Timely manner" is defined as servicing the recovery workload within two TPs for a given maintenance unit. To meet this criterion the recovery workload at the end of one TP must be serviced in the next time period. The reason for this explanation of "timely manner" is to account for the maximum time of 96 minutes it takes for a recovery vehicle to assist in the recovery of a damaged weapon system or vehicle. If a vehicle requires an assisted recovery during the last half of the current TP, that vehicle would not reach the designated maintenance area until the next TP. The two recovery vehicles modeled are the improved recovery vehicle (M88) and a generic recovery vehicle

(HMTWRECKER) which represent all other recovery vehicles which are not M88s. Table M-4 provides an overview of both recovery vehicle's status for the scenario where:

Initial Strength (stgn) is the assigned density at the start of the scenario.

End Strength (stgn) is the number operational at the end of the scenario.

End Availability is the percentage of initial strength available less the number destroyed or abandoned at the end of the scenario.

| M88 | | | | HMTWRECKER | | | |
|---------|--------------|----------|------------------|------------|--------------|----------|------------------|
| Unit ID | Initial Stgn | End Stgn | End Availability | Unit ID | Initial Stgn | End Stgn | End Availability |
| B3000DC | 2 | 1.9 | 95 | B3000DC | 1 | 1.0 | 100 |
| B3000MX | 3 | 2.6 | 87 | B3000LH | 1 | 1.0 | 100 |
| B3001DC | 1 | 0.7 | 70 | B3000M2 | 1 | 1.0 | 100 |
| B3001H2 | 4 | 3.5 | 88 | B3000MX | 3 | 3.0 | 100 |
| B3002H2 | 4 | 2.6 | 65 | B3001H2 | 1 | 1.0 | 100 |
| B3003DC | 1 | 0.8 | 80 | B3002H2 | 1 | 0.7 | 70 |
| B3003H2 | 4 | 3.6 | 90 | B3003H2 | 1 | 1.0 | 100 |
| B3010MX | 3 | 2.6 | 87 | B30100H | 2 | 2.0 | 100 |
| B3011MX | 7 | 0.8 | 11 | B3010MX | 4 | 3.9 | 98 |
| B3012MX | 7 | 6.0 | 86 | B3011MX | 2 | 0.6 | 30 |
| B3013AR | 6 | 5.1 | 85 | B3012MX | 2 | 1.9 | 95 |
| B3020MX | 3 | 2.7 | 90 | B3020MX | 4 | 3.8 | 95 |
| B3021MX | 7 | 5.6 | 80 | B3021MX | 2 | 1.9 | 95 |
| B3022MX | 7 | 5.2 | 74 | B3022MX | 2 | 1.9 | 95 |
| B3023AR | 6 | 4.9 | 82 | B3030AR | 4 | 3.8 | 95 |
| B3030AR | 3 | 2.6 | 87 | B3033MX | 2 | 1.9 | 95 |
| B3031AR | 6 | 4.7 | 78 | B30A00H | 1 | 1.0 | 100 |
| B3032AR | 6 | 5.0 | 83 | B30C00H | 1 | 1.0 | 100 |
| B3033MX | 7 | 5.7 | 82 | | | | |

M88 and HMTWRECKER Ending Availabilities
Table M-4

The "end availability" is a reliable indicator of availability and recovery support throughout the scenario. Table M-5 provides the combined recovery operations for all divisional maintenance units by TP.

| TP | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|----------------|------|------|------|------|------|------|------|------|
| # RECOV. | 16.9 | 20.3 | 19.5 | 18.5 | 17.7 | 17 | 16.4 | 15.8 |
| WAITING RECOV. | 4.3 | 4.3 | 4.1 | 3.9 | 3.8 | 3.7 | 3.5 | 3.4 |
| TP | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
| # RECOV. | 15.1 | 14.6 | 13.9 | 17.4 | 19 | 13.5 | 18.9 | |
| WAITING RECOV. | 3.3 | 3.1 | 3 | 6.3 | 3.6 | 4.3 | 6.3 | |

Recovery Operations for All Divisional Maintenance Units
Table M-5

2 All maintenance facilities recovered their recovery workload in a timely manner. Table M-6 lists the recovery workload for all maintenance units by recovery vehicle type.

| Maintenance | Recovered by | | | Maintenance | Recovered by | | |
|-------------|--------------|-----|-------|-------------|--------------|-----|-------|
| Unit | HMTWRECKER | M88 | TOTAL | Unit | HMTWRECKER | M88 | TOTAL |
| B3000DC | 1 | 1 | 2 | B3012MX | 1 | 11 | 12 |
| B3000LH | 0 | 0 | 0 | B3013AR | 0 | 11 | 11 |
| B3000M2 | 1 | 0 | 1 | B3020MX | 21 | 33 | 54 |
| B3000MX | 80 | 32 | 112 | B3021MX | 1 | 13 | 14 |
| B3001DC | 0 | 3 | 3 | B3022MX | 1 | 14 | 15 |
| B3001H2 | 7 | 4 | 11 | B3023AR | 0 | 12 | 12 |
| B3002DC | 0 | 3 | 3 | B3030AR | 20 | 3 | 23 |
| B3002H2 | 8 | 6 | 14 | B3031AR | 0 | 16 | 16 |
| B3003DC | 0 | 5 | 5 | B3032AR | 0 | 12 | 12 |
| B3003H2 | 9 | 4 | 13 | B3033MX | 1 | 14 | 15 |
| B30100H | 53 | 0 | 53 | B30A00H | 0 | 0 | 0 |
| B3010MX | 22 | 35 | 57 | B30C00H | 0 | 0 | 0 |
| B3011MX | 3 | 23 | 26 | | | | |

Recovery Workload (by M88 and HMTWRECKER)
Table M-6

3 Conclusion:

No recovery shortfalls existed at any unit for the M88 or HMTWRECKER.

(b) Recovery - Personnel.

The recovery of injured personnel is implied; therefore, injured personnel do not require a recovery vehicle for transport from the battlefield to a medical facility. This phenomenon negates the possibility of a backlog of injured personnel needing recovery. Hence, personnel RTC will never be impeded by recovery assets.

(c) Evacuation - Weapons.

1 Evacuation support is performed in the scenario by HETs and a generic evacuation vehicle. The purpose of the generic evacuation vehicle is to represent the backhaul capability of other transporters. The analysis focuses on the HETs because they are considered potential constraints on evacuation. All but five of the key weapon systems utilize HETs for evacuation. The exceptions are AH64D, RAH66, RAH66D, AVENGER, and the PATRIOT. Only the performance of HETs is addressed. Weapon system evacuations are performed in a "timely manner" if damaged weapon systems are evacuated to the designated area (corps or division) within two TPs of the sustained damage.

2 Evacuation in this scenario is supported at the division area (unit B3000MX) and at the corps area (unit B000000) with 24 and 30 HETs assigned, respectively. Evacuations occur for two reasons:

- designation of maintenance support at higher support levels.
- lengthy clockhour repair times (any vehicle or weapon system that requires more than seven clockhours to repair will be sent to the corps support area (forward) so it will not 'tie up' mechanics at the ORG level with maintenance work that requires a considerable amount of time).
- maintenance overflow (maintenance overflow occurs when the number of hours needed to repair awaiting weapon systems exceeds a maintenance man hour threshold set for a maintenance unit).

3 Across the scenario, a maximum of ten percent of the corps area's HETs and twenty percent of the division area's HETs were not available at any given TP, all due to RAM damage.

4 There were 173 vehicle and weapon system evacuations to the corps area which required a HET (refer to table M-7). These vehicles and weapon systems included 138 AVLBs, 20 M1A2/120s, 7 M3A2s, 3 M2A2/TOWs, and 3 M577. All of these vehicles and weapon systems were evacuated to the corps area in a "timely manner."

| TP | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|----------------|------|------|------|------|------|------|------|------|
| # RECOV. | 6.9 | 17.4 | 17.8 | 16.7 | 14.0 | 12.5 | 14.1 | 12.7 |
| WAITING RECOV. | 6.0 | 9.5 | 10.0 | 10.1 | 9.4 | 9.9 | 11.5 | 9.2 |
| TP | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
| # RECOV. | 11.1 | 10.3 | 9.1 | 7.9 | 8.2 | 7.5 | 6.8 | |
| WAITING RECOV. | 8.4 | 8.4 | 7.3 | 7.6 | 8.0 | 7.0 | 6.7 | |

Evacuation Workload - Corps Area
Table M-7

5 There were 54 vehicle and weapon system evacuations to the division area which required a HET (refer to table M-8). These 54 vehicles and weapon systems were 35 AVLBs, 10 M1A2s, 7 M2A2/TOWs, and 1 M577. All 54 of these weapon systems were evacuated to the division area in a "timely manner."

| TP | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|----------------|-----|-----|-----|-----|-----|-----|-----|-----|
| # RECOV. | 3.2 | 4.9 | 4.4 | 3.9 | 3.9 | 3.4 | 3.0 | 3.2 |
| WAITING RECOV. | 0.4 | 0.3 | 0.3 | 0.3 | 0.3 | 0.4 | 0.5 | 0.6 |
| TP | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
| # RECOV. | 2.9 | 2.4 | 2.5 | 4.5 | 5.3 | 4.3 | 2.2 | |
| WAITING RECOV. | 0.6 | 0.7 | 0.9 | 2.0 | 0.8 | 0.3 | 0.4 | |

Evacuation Workload - Division Area
Table M-8

6 Conclusion:

Evacuation is not a constraint on weapon system RTC.

(d) Evacuation - Personnel.

This function was not represented in the VIC model, therefore, no personnel evacuation output data was available for analysis.

(e) Repair - ground based weapons.

1 Sufficient repair support is determined by the availability of required mechanic types at the supporting maintenance facility for ORG/DS and GS levels. For the most part, FORCE XXI mechanics in the DISCOM are modular in that they can repair both ORG and DS level damaged vehicles. Table M-9 shows, for assigned ORG/DS level mechanics, the maximum MMH percentage utilized for each of the 29 maintenance facilities across the scenario. When this percentage is 100 sufficient mechanics were not available to service the workload (note shaded cells) at some point during the scenario.

2 There was never an instance of armament or automotive mechanics becoming 100 percent utilized within the Conservative Heavy Division (any unit label B3*****).


| Unit Name | Armament | | Automotive | | Helicopter | | Medical | |
|-----------|----------|------|------------|------|------------|------|---------|------|
| | Util. % | Str. | Util. % | Str. | Util. % | Str. | Util. % | Str. |
| B000000 | 10 | 78 | 100 | 100 | | | 42 | 65 |
| B000CFC | 0 | 185 | 3 | 658 | | | 2 | 875 |
| B300002 | 0 | 27 | 10 | 12 | | | 37 | 5 |
| B3000AD | 21 | 5 | 29 | 10 | | | 100 | 2 |
| B3000DC | 49 | 10 | 78 | 14 | | | 7 | 18 |
| B3000LH | 1 | 2 | 1 | 21 | 8 | 85 | 61 | 3 |
| B3000M2 | 2 | 15 | 6 | 40 | | | 26 | 11 |
| B3000MX | 6 | 116 | 19 | 241 | | | 18 | 130 |
| B3001DC | 30 | 5 | 15 | 9 | | | 21 | 2 |
| B3001H2 | 0 | 8 | 26 | 17 | | | 27 | 12 |
| B3002DC | 28 | 5 | 13 | 9 | | | 21 | 2 |
| B3002H2 | 0 | 8 | 27 | 17 | | | 28 | 12 |
| B3003DC | 69 | 5 | 10 | 9 | | | 21 | 2 |
| B3003H2 | 0 | 8 | 32 | 17 | | | 27 | 12 |
| B30100H | 0 | 22 | 5 | 184 | 0 | 228 | 15 | 22 |
| B3010MX | 5 | 29 | 40 | 96 | | | 21 | 57 |
| B3011MX | 71 | 32 | 78 | 38 | | | 13 | 51 |
| B3012MX | 5 | 32 | 28 | 38 | | | 8 | 51 |
| B3013AR | 6 | 39 | 28 | 35 | | | 9 | 42 |
| B3020MX | 2 | 29 | 26 | 96 | | | 11 | 57 |
| B3021MX | 11 | 32 | 28 | 38 | | | 9 | 51 |
| B3022MX | 12 | 32 | 28 | 38 | | | 8 | 51 |
| B3023AR | 15 | 39 | 28 | 35 | | | 9 | 42 |
| B3030AR | 1 | 29 | 8 | 96 | | | 9 | 57 |
| B3031AR | 6 | 39 | 28 | 35 | | | 9 | 42 |
| B3032AR | 6 | 39 | 28 | 35 | | | 9 | 42 |
| B3033MX | 6 | 32 | 28 | 38 | | | 8 | 51 |
| B30A00H | 2 | 2 | 11 | 17 | 4 | 120 | 100 | 3 |
| B30C00H | 1 | 2 | 6 | 15 | 1 | 98 | 51 | 3 |

Utilization and Initial Strength by ORG/DS Level Mechanics
Table M-9

3 In general, for those facilities with less than 100% utilization at the end of a TP, sufficient maintenance resources were always available. There were only minor exceptions when very small fractional workloads were evacuated due to backlog status and the MMH utilization was not 100%. Any under-utilized resources are not necessarily "excesses" but are indicators of the magnitude of the workload for this scenario. Force structure implications are not addressed in this report.

4 Figure M-1 shows the ORG/DS automotive mechanic utilization for the FSC supporting the 1st mechanized infantry battalion of the 1st brigade (unit B3011MX). This was the only unit within the DISCOM that had any maintenance problems.

- For this FSC (unit B3011MX) the highest automotive mechanic utilization (78 percent) occurred during TP 15 (see Figure M-1). Maintenance overflow occurred at this maintenance facility with the following list of vehicles had to be recovered to the 1st brigade's BSC twelve one-ton cargo trucks, six LMTVs, four MTVs, three ambulances, two M88s, one BCMDVEH, one HMTWRECKER, and one M113. The largest buildup of unserviced weapon systems occurred during TP 13 with three M1A2/120s and two M2A3/TOWs waiting for automotive mechanics to become available. By the end of the scenario the number of weapons systems waiting for automotive repair was negligible.



Automotive Mechanic Utilization the FSC supporting the 1st battalion of the 1st brigade (unit B3011MX)
Figure M-1

- Table M-10 shows the GS level mechanic utilization at the CORPS level.

| Unit Name | Armament | | Automotive | | Helicopter | | Medical | |
|-----------|----------|------|------------|------|------------|------|---------|------|
| | Util. % | Str. | Util. % | Str. | Util. % | Str. | Util. % | Str. |
| CSB(DS) | 71 | 50 | 100 | 90 | 1 | 271 | 31 | 63 |
| CORPS(R) | 0 | 5 | 25 | 18 | | | | |

Utilization and Initial Strength by GS Level Mechanics
Table M-10

- The automotive mechanics at the CSB(DS) were 100 percent utilized from TP 4 on. The largest buildup of unserviced weapon systems occurred during TP 14 with 28 M88s, 18 M2A3/TOWs, 10 M1A2s, 9 MLRS, 8 FSCS/45s, and 2 CRUSADERS. So with 90 automotive mechanics, the CSB(DS) had difficulties with the workload produce during this scenario.

- Table M-11 shows the GS level mechanic utilization at the CORPS level. Only the medical team was fully utilized during the scenario.

| Unit Name | Armament | | Automotive | | Helicopter | | Medical | |
|-----------|----------|------|------------|------|------------|------|---------|------|
| | Util. % | Str. | Util. % | Str. | Util. % | Str. | Util. % | Str. |
| CORPS(R) | 7 | 60 | 9 | 200 | 0 | 130 | 100 | 875 |

Utilization and Initial Strength by GS Level Mechanics
Table M-11

5 Conclusion:

No maintenance units within the DISCOM constrained key weapon system RTC.

(f) Repair - helicopters.

Note: The AH64D (Apache) and the RAH66D & RAH66 (Comanche) are the systems represented by the helicopter weapon system category.

1 Sufficient helicopter repair support is determined by the availability of required helicopter mechanics at the supporting maintenance facility. The number of helicopter mechanics assigned to the helicopter battalions, the corps area, and division area can be found in tables M-9 through M-11. Note from these tables that none of the helicopter maintenance facilities had their mechanics 100% utilized during any TP of the scenario.

2 Recovery - The AH64D, RAH66, and the RAH66D do not require assisted recovery. If one of these helicopters receives non-catastrophic damage, that helicopter is assumed to self-recover. Helicopter RTC will never be impeded by recovery assets.

3 Evacuation - The AH64D, RAH66, and the RAH66D do not require a HET for evacuation. Instead, a generic evacuation vehicle is used to evacuate AH64Ds and RAH66Ds. The availability of HETs does not hamper the process of helicopter evacuation.

4 Conclusion:

None of the three CSS assets (recovery, evacuation, and repair) restricted helicopter RTC during the scenario.

(g) Medical treatment.

1 Personnel can be in one of the following three categories: combat ready, medical treatment process, or KIA. When injured personnel arrive at a medical facility, they receive treatment immediately, have to wait for the next available medic, or have to be evacuated to a higher echelon because of the severity of the wound. After treatment, injured personnel are returned to their respective unit. At TP 15, the theater's Blue troop force was at 90%, its lowest availability during any TP of the scenario (refer to table M-12).

| TP | Combat Ready | Being Treated | KIA | % AVAIL |
|----|--------------|---------------|-----|---------|
| 0 | 15,772 | 0 | 0 | 100 |
| 1 | 15,697 | 75 | 0 | 100 |
| 2 | 15,617 | 155 | 0 | 99 |
| 3 | 15,540 | 232 | 0 | 99 |
| 4 | 15,461 | 311 | 0 | 98 |
| 5 | 15,382 | 390 | 0 | 98 |
| 6 | 15,305 | 467 | 0 | 97 |
| 7 | 15,229 | 543 | 0 | 97 |
| 8 | 15,151 | 621 | 0 | 96 |
| 9 | 15,076 | 696 | 0 | 96 |
| 10 | 15,000 | 772 | 0 | 95 |
| 11 | 14,920 | 851 | 1 | 95 |
| 12 | 14,776 | 972 | 24 | 94 |
| 13 | 14,688 | 1,055 | 29 | 93 |
| 14 | 14,422 | 1,292 | 58 | 92 |
| 15 | 14,163 | 1,493 | 116 | 90 |

Theater Personnel Profile
Table M-12

2 During the course of the scenario, the majority of personnel that are not combat ready are being treated or awaiting treatment at the corps area. When injured personnel have to be evacuated to corps, their severe injuries take approximately six days to treat; therefore, those persons will not return to duty for the remaining part of the scenario.

3 While the combined totals of the theater's Blue troop forces always remained above the 80% availability sufficiency criterion, a single unit (unit B3011MX) fell below this criterion for two or more consecutive TPs. This unit is listed in table M-13 along with their troop combat availability percentage. The increase of combat intensity in the later part of the scenario and the treatment time of injured

troops evacuated to the corps area are the two factors that contribute to the low troop availability at this unit.

| TP | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|---------|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| B3011MX | 100 | 99 | 99 | 98 | 98 | 97 | 97 | 96 | 96 | 95 | 95 | 84 | 81 | 64 | 51 |

Percentage of Personnel Available
Table M-13

4 Conclusion:

Medical repair teams organic to echelons lower than division did not constrain personnel RTC.

(2) Key Weapon Availability.

(a) Up to this point the analysis has addressed individual CSS support services (recovery, evacuation, repair, medical treatment) and their impact on RTC. With the exceptions noted, for the most part each of these support services was sufficient for the available workloads.

(b) The following section of the report, in effect, examines the cumulative effects of CSS services by looking at the availability of key weapons. Tables M-16 through M-26 provide unit level overviews for each key weapon system.

1 Each table (M-16 through M-26) contains the following information:

- Initial Strength (stgn) - weapon system density at the start of the scenario.
- End Strength (stgn) - weapon system density at the end of the scenario.
- Permanent Losses (K-kills) - catastrophic kills and abandonments.
- End % availability - weapon system availability at the end of the scenario.

This availability calculation excludes permanent losses in conformance with the earlier described sufficiency criteria. Permanent losses are excluded because their occurrence is independent of how well (or poorly) CSS performs.

2 Two phenomena appearing in the following tables warrant discussion:

a A "dead unit" is indicated when the "end strength" and "availability" are zero. A "dead unit" occurs when significant unit resources are decimated and that unit can no longer effectively function. Its surviving resources, damaged and undamaged, are distributed to repair or other units requiring weapons, respectively. The row in each table for dead units is shaded.

b One would expect the "end strength" to always be smaller than initial strength if there were permanent losses. This is not always the case because of the need based reissue of repaired (and crewed) weapons. Depending on the current available strength of a weapon, reissues are distributed proportionally higher to those units with the greatest need (lowest current strength) and not to the unit which originally "owned" the weapon.

(c) Results:

1 All weapon systems meet the availability sufficiency criteria (80%) except for the following cases listed in table M-14.

| Weapon System | Unit | End % Avail | Weapon System | Unit | End % Avail |
|---------------|---------|-------------|---------------|---------|-------------|
| M1A2/120 | B3001DC | 46 | FSCS/45 | B3001DC | 62 |
| M1A2/120 | B3003DC | 21 | FSCS/45 | B3002DC | 0 |
| M1A2/120 | B3011MX | 0 | FSCS/45 | B3003DC | 32 |
| M1A2/120 | B3012MX | 63 | FSCS/45 | B3010RE | 65 |
| M1A2/120 | B3013AR | 63 | FSCS/45 | B3011MX | 0 |
| M1A2/120 | B3021MX | 59 | FSCS/45 | B3012MX | 68 |
| M1A2/120 | B3022MX | 50 | FSCS/45 | B3013AR | 68 |
| M1A2/120 | B3023AR | 62 | FSCS/45 | B3020RE | 74 |
| M1A2/120 | B3031AR | 42 | FSCS/45 | B3021MX | 62 |
| M1A2/120 | B3032AR | 63 | FSCS/45 | B3022MX | 22 |
| M2A3/TOW | B3010MX | 67 | FSCS/45 | B3023AR | 67 |
| M2A3/TOW | B3011MX | 0 | FSCS/45 | B3030RE | 86 |
| M2A3/TOW | B3012MX | 68 | FSCS/45 | B3031AR | 68 |
| M2A3/TOW | B3013AR | 68 | FSCS/45 | B3032AR | 66 |
| M2A3/TOW | B3021MX | 53 | FSCS/45 | B3033MX | 75 |
| M2A3/TOW | B3022MX | 59 | CRUSADER-D | B3001H2 | 68 |
| M2A3/TOW | B3023AR | 67 | CRUSADER-D | B3002H2 | 70 |
| M2A3/TOW | B3030AR | 74 | CRUSADER-D | B3003H2 | 78 |
| M2A3/TOW | B3031AR | 45 | AH64D | B30A00H | 29 |
| M2A3/TOW | B3032AR | 66 | RAH66 | B3000LH | 35 |
| FSCS/45 | B3000DC | 92 | RAH66D | B30A00H | 33 |

Units with Below 80 Percent of any Key Weapon System
Table M-14

2 The following table lists the only unit that was rendered combat ineffective ("dead") during the scenario, the time that the unit became ineffective, and the major weapon system(s) organic to that unit.

| Ineffective "Dead" Unit | Time | Major Weapon Systems |
|-------------------------|-------|----------------------|
| B3002DC | 52.24 | M1A2/120, FSCS/45 |

Unit Rendered Combat Ineffective During the Scenario
Table M-15

3 Conclusion:

The CSS system did not constrain weapon system availability.

Reference (b).1). of Section (2), Key Weapon Availability -- end % availability is the weapon system availability at the end of the scenario. This availability calculation excludes permanent losses in conformance with the earlier described sufficiency criteria. Permanent losses are excluded because their occurrence is independent of how well (or poorly) CSS performs.

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B3001DC | 9 | 4.0 | 0.2 | 46 |
| B3002DC | 9 | 0.0 | 0.7 | 0 |
| B3003DC | 9 | 1.6 | 1.1 | 21 |
| B3011MX | 14 | 0.0 | 2.4 | 0 |
| B3012MX | 14 | 8.6 | 0.3 | 63 |
| B3013AR | 30 | 18.5 | 0.7 | 63 |
| B3021MX | 14 | 8.3 | 0.1 | 59 |
| B3022MX | 14 | 6.7 | 0.7 | 50 |
| B3023AR | 30 | 18.5 | 0.1 | 62 |
| B3031AR | 30 | 12.1 | 1.5 | 42 |
| B3032AR | 30 | 18.8 | 0.0 | 63 |
| B3033MX | 14 | 11.1 | 0.1 | 80 |
| Total Permanent Losses | | | 8.0 | |

M1A2/120 Status
Table M-16

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B3010MX | 3 | 2.0 | 0.0 | 67 |
| B3011MX | 30 | 0.0 | 7.1 | 0 |
| B3012MX | 30 | 20.1 | 0.4 | 68 |
| B3013AR | 14 | 9.4 | 0.2 | 68 |
| B3020MX | 3 | 2.4 | 0.1 | 82 |
| B3021MX | 30 | 15.0 | 1.4 | 53 |
| B3022MX | 30 | 17.0 | 1.1 | 59 |
| B3023AR | 14 | 9.3 | 0.0 | 67 |
| B3030AR | 3 | 2.2 | 0.0 | 74 |
| B3031AR | 14 | 5.9 | 1.0 | 45 |
| B3032AR | 14 | 9.2 | 0.0 | 66 |
| B3033MX | 30 | 25.9 | 0.0 | 86 |
| Total Permanent Losses | | | 11.4 | |

M2A3/TOW Status
Table M-17

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B300AAD | 2 | 1.9 | 0.0 | 93 |
| B300BAD | 2 | 2.0 | 0.0 | 98 |
| B300CAD | 2 | 2.0 | 0.0 | 99 |
| Total Permanent Losses | | | 0.0 | |

M3A3/TOW Status
Table M-18

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B300AAD | 8 | 7.1 | 0.0 | 89 |
| B300BAD | 8 | 7.2 | 0.0 | 91 |
| B300CAD | 8 | 7.3 | 0.0 | 92 |
| Total Permanent Losses | | | 0.0 | |

BSFV-E Status
Table M-19

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B3000DC | 2 | 1.8 | 0.1 | 92 |
| B3001DC | 9 | 5.4 | 0.3 | 62 |
| B3002DC | 9 | 0.0 | 0.7 | 0 |
| B3003DC | 9 | 2.5 | 1.4 | 32 |
| B3010RE | 7 | 4.2 | 0.5 | 65 |
| B3011MX | 6 | 0.0 | 1.7 | 0 |
| B3012MX | 6 | 4.0 | 0.1 | 68 |
| B3013AR | 6 | 4.0 | 0.1 | 68 |
| B3020RE | 7 | 5.2 | 0.0 | 74 |
| B3021MX | 6 | 3.6 | 0.2 | 62 |
| B3022MX | 6 | 1.1 | 1.2 | 22 |
| B3023AR | 6 | 4.0 | 0.0 | 67 |
| B3030RE | 7 | 6.0 | 0.0 | 86 |
| B3031AR | 6 | 4.1 | 0.0 | 68 |
| B3032AR | 6 | 4.0 | 0.0 | 66 |
| B3033MX | 6 | 4.4 | 0.1 | 75 |
| Total Permanent Losses | | | 6.4 | |

*FSCS/45 Status
Table M-20

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B3000LH | 2 | 1.9 | 0.0 | 95 |
| B3000MX | 3 | 2.8 | 0.0 | 94 |
| B3004EN | 4 | 3.7 | 0.0 | 93 |
| B300AAD | 6 | 5.6 | 0.0 | 93 |
| B300BAD | 6 | 5.7 | 0.0 | 94 |
| B300CAD | 6 | 5.7 | 0.0 | 95 |
| B300DSB | 3 | 2.8 | 0.0 | 94 |
| B301FSB | 2 | 1.9 | 0.0 | 95 |
| B302FSB | 2 | 1.9 | 0.0 | 95 |
| B303FSB | 2 | 1.9 | 0.0 | 95 |
| B30A00H | 2 | 1.9 | 0.0 | 95 |
| B30C00H | 2 | 1.9 | 0.0 | 95 |
| Total Permanent Losses | | | 0.0 | |

AVENGER Status
Table M-21

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B300AM2 | 9 | 8.7 | 0.0 | 96 |
| B300BM2 | 9 | 8.8 | 0.0 | 98 |
| Total Permanent Losses | | | 0.0 | |

MLRS-D Status
Table M-22

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B3001H2 | 18 | 12.1 | 0.3 | 68 |
| B3002H2 | 18 | 12.6 | 0.0 | 70 |
| B3003H2 | 18 | 14.1 | 0.0 | 78 |
| Total Permanent Losses | | | 0.3 | |

CRUSADER-D Status
Table M-23

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B30A00H | 15 | 4.3 | 0.0 | 29 |
| Total Permanent Losses | | | 0.0 | |

AH64D Status
Table M-24

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B3000LH | 24 | 8.48 | 0 | 35 |
| Total Permanent Losses | | | 0.0 | |

RAH66 Status
Table M-25

| Unit ID | Initial Stgn | End Stgn | K-Kills | End % Avail |
|------------------------|--------------|----------|---------|-------------|
| B30A00H | 9 | 3.0 | 0.0 | 33 |
| Total Permanent Losses | | | 0.0 | |

RAH66D Status
Table M-26

(3) CSS Workloads. The following CSS workloads are provided to show the type and magnitude of workload serviced by each unit.

(a) Recovery and evacuation vehicle workload. The second and third columns in table M-27 indicate the number of vehicles that required assisted recovery from their owning unit. The fourth through seventh columns show the number of vehicles that required evacuation 'in' and 'out' of a higher echelon maintenance unit; also indicated is whether or not the vehicle required a HET for evacuation.

| Maint Unit | Total # of assisted recoveries | | # EVAC'D IN | | # EVAC'D OUT | |
|------------|--------------------------------|------|-------------|--------|--------------|--------|
| | HMTWRECKER | M88 | TOTAL | w/ HET | TOTAL | w/ HET |
| B3000DC | 0.8 | 1.4 | 43.8 | 39.8 | 8.4 | 1.9 |
| B3000LH | 0.3 | | | | 0.0 | |
| B3000M2 | 1.3 | | | | 0.0 | 0.0 |
| B3000MX | 79.6 | 31.8 | | | 50.4 | 50.4 |
| B3001DC | | 3.2 | | | 4.4 | 2.5 |
| B3001H2 | 6.5 | 4.2 | | | 0.0 | 0.0 |
| B3002DC | | 2.6 | | | 3.3 | 1.8 |
| B3002H2 | 7.6 | 5.6 | | | 1.5 | 0.3 |
| B3003DC | | 5.3 | | | 6.8 | 4.4 |
| B3003H2 | 9.2 | 4.5 | | | 0.0 | 0.0 |
| B30100H | 52.6 | | | | 0.0 | 0.0 |
| B3010MX | 21.9 | 42.3 | | | 17.1 | 17.1 |
| B3011MX | 2.6 | 23.3 | | | 44.5 | 3.2 |
| B3012MX | 1.4 | 11.4 | | | 0.0 | 0.0 |
| B3013AR | | 11.1 | | | 0.0 | 0.0 |
| B3020MX | 21.1 | 33.0 | | | 18.3 | 18.3 |
| B3021MX | 1.4 | 13.0 | | | 0.0 | 0.0 |
| B3022MX | 1.4 | 13.6 | | | 0.0 | 0.0 |
| B3023AR | | 11.6 | | | 0.0 | 0.0 |
| B3030AR | 20.0 | 2.7 | | | 0.0 | 0.0 |
| B3031AR | | 15.5 | | | 0.0 | 0.0 |
| B3032AR | | 12.1 | | | 0.0 | 0.0 |
| B3033MX | 1.5 | 14.4 | | | 0.0 | 0.0 |
| B30A00H | 0.5 | | | | 0.0 | |
| B30C00H | 0.4 | | | | 0.0 | |

Recovery and Evacuation Workload
Table M-27

(b) Medical team workload. Table M-28 shows the number of personnel that arrived at a medical facility during the scenario due to combat and non-combat (DNBI) actions. The last column displays the number of treatment man hours expended by all medical teams.

| MEDICAL UNIT | CBT MEDICAL RECOVERED | DNBI MEDICAL RECOVERED | MMH EXPENDED | MEDICAL UNIT | CBT MEDICAL RECOVERED | DNBI MEDICAL RECOVERED | MMH EXPENDED |
|--------------|-----------------------|------------------------|--------------|--------------|-----------------------|------------------------|--------------|
| B000000 | 379 | 309 | 958.6 | B3010MX | 0 | 67 | 149.3 |
| B000CFC | 1,913 | 1,586 | 18,833.2 | B3011MX | 6 | 23 | 58.8 |
| B300002 | 0 | 10 | 22.7 | B3012MX | 0 | 24 | 54.0 |
| B3000AD | 0 | 17 | 29.6 | B3013AR | 0 | 22 | 48.9 |
| B3000DC | 0 | 9 | 20.8 | B3020MX | 0 | 33 | 72.6 |
| B3000LH | 0 | 15 | 33.9 | B3021MX | 1 | 24 | 54.4 |
| B3000M2 | 0 | 16 | 35.0 | B3022MX | 0 | 24 | 54.1 |
| B3000MX | 0 | 131 | 289.7 | B3023AR | 0 | 22 | 49.0 |
| B3001DC | 0 | 2 | 5.1 | B3030AR | 0 | 29 | 64.0 |
| B3001H2 | 0 | 18 | 40.5 | B3031AR | 2 | 22 | 49.0 |
| B3002DC | 0 | 2 | 4.5 | B3032AR | 0 | 22 | 48.9 |
| B3002H2 | 0 | 18 | 40.5 | B3033MX | 0 | 25 | 54.1 |
| B3003DC | 0 | 2 | 5.6 | B30A00H | 0 | 16 | 34.3 |
| B3003H2 | 0 | 18 | 40.4 | B30C00H | 0 | 12 | 27.8 |
| B30100H | 0 | 34 | 76.2 | | | | |

Medical Unit Workload
Table M-28

(c) Maintenance team workload. Table M-29 shows the number of vehicles (both ground and air) that were recovered to a maintenance facility during the scenario. The last four columns display the number of maintenance man hours expended on ground and air vehicles and the estimated number of maintenance man hours required at TP 10 to repair all vehicles at the maintenance facilities.

| MAINT UNIT | # VEHICLES RECOVERED | | GROUND VEHICLES | | HELICOPTERS | |
|------------|----------------------|------------|-----------------|------------|--------------|------------|
| | CBT DAMAGE | RAM DAMAGE | MMH EXPENDED | MMH NEEDED | MMH EXPENDED | MMH NEEDED |
| CSB(DS) | 442.6 | 1,038.6 | 4,249.4 | 4,357.9 | 79.4 | 4.1 |
| CORPS(R) | 1,945.9 | 1,892.6 | 830.3 | 147.1 | | |
| B300002 | 0.0 | 17.3 | 10.4 | 0.1 | | |
| B3000AD | 0.0 | 34.7 | 29.5 | 0.5 | | |
| B3000DC | 0.0 | 20.2 | 83.0 | 1.0 | | |
| B3000LH | 0.0 | 34.4 | 6.6 | 0.1 | 71.4 | 0.3 |
| B3000M2 | 0.0 | 31.6 | 23.2 | 0.3 | | |
| B3000MX | 0.0 | 350.4 | 436.0 | 54.9 | | |
| B3001DC | 2.7 | 8.8 | 21.8 | 0.6 | | |
| B3001H2 | 0.1 | 38.0 | 38.7 | 0.9 | | |
| B3002DC | 2.4 | 8.2 | 16.9 | | | |
| B3002H2 | 27.5 | 37.9 | 38.9 | 40.4 | | |
| B3003DC | 7.0 | 9.0 | 26.7 | 2.9 | | |
| B3003H2 | 0.0 | 41.0 | 43.1 | 1.0 | | |
| B30100H | 0.0 | 109.8 | 109.1 | 0.4 | | |
| B3010MX | 2.6 | 169.8 | 292.6 | 99.0 | | |
| B3011MX | 82.0 | 52.7 | 197.8 | 0.0 | | |
| B3012MX | 0.0 | 56.7 | 106.9 | 3.3 | | |
| B3013AR | 0.0 | 54.3 | 115.1 | 4.2 | | |
| B3020MX | 0.0 | 122.7 | 225.0 | 53.5 | | |
| B3021MX | 4.6 | 57.1 | 109.0 | 16.2 | | |
| B3022MX | 5.1 | 57.2 | 109.1 | 12.9 | | |
| B3023AR | 3.8 | 54.9 | 117.9 | 10.5 | | |
| B3030AR | 0.0 | 78.7 | 79.8 | 1.7 | | |
| B3031AR | 9.2 | 54.9 | 116.7 | 8.1 | | |
| B3032AR | 0.0 | 54.9 | 116.2 | 6.2 | | |
| B3033MX | 1.5 | 59.8 | 119.3 | 7.2 | | |
| B30A00H | 0.0 | 40.7 | 15.7 | 0.1 | 44.4 | 0.4 |
| B30C00H | 0.0 | 25.0 | 14.6 | 0.1 | 17.4 | 0.3 |

Maintenance Unit Workload
Table M-29

(4) Observations.

- 1) No recovery shortfalls existed at any unit for the M88 or HMIWRECKER.
- 2) Evacuation is not a constraint on weapon system RTC.
- 3) No maintenance units within the DISCOM constrained key weapon system RTC.
- 4) None of the three CSS assets (recovery, evacuation, and repair) restricted helicopter RTC during the scenario.
- 5) Medical repair teams organic to echelons lower than division did not constrain personnel RTC.
- 6) The CSS system did not constrain weapon system availability.

6. Supply Analysis.

a. This analysis assesses the CSS system's capability to support combat and combat support units for the defined scenario. The CSS units must fill requests for replenishment stockages in a "timely fashion;" failure to do so can be attributed to lack of transporters, lack of stockages, long order-to-delivery times, or a combination of the three.

b. Analysis. This analysis is structured into two parts: supply class III and supply class V.

(1) Supply Class III.

(a) Requirement. For the scenario, the requirement for class III (petroleum) was found by summing the consumption (quantities "used" plus quantities "lost") of all maneuver units (CSS units were excluded from this computation) during each TP. Calculated in "gallons (gals)," the requirement for class III for the length of the scenario is presented in table L-1.

The consumption of supplies generates a requirement for stocks of supply types as well as transportation assets to deliver the replenishments to maneuver unit stockages. Consumption is translated into an order for materiel. Each order levies upon the CSS system a requirement for existing stocks and transportation assets. The authorized amount declines with time due to the attrition of weapon systems. Each weapon system has an authorized amount of specific supply types, and the authorized stockage is reduced as systems are killed. Table L-1 identifies the area of operation (AO) stockage levels and activities for class III: 1) amounts used; 2) amounts lost; and 3) amounts consumed (the requirement).

| TP | USED GALS | LOST GALS | REQUIREMENT CONSUMED |
|-------|--------------|--------------|-------------------------|
| 0 | 0 | 0 | 0 |
| 1 | 47,407 | 896 | 48,303 |
| 2 | 25,277 | 1,389 | 26,666 |
| 3 | 19,402 | 305 | 19,707 |
| 4 | 19,191 | 178 | 19,369 |
| 5 | 19,530 | 208 | 19,738 |
| 6 | 23,769 | 140 | 23,909 |
| 7 | 27,581 | 659 | 28,240 |
| 8 | 21,719 | 119 | 21,838 |
| 9 | 25,822 | 14 | 25,836 |
| 10 | 20,974 | 4 | 20,978 |
| 11 | 81,130 | 364 | 81,494 |
| 12 | 38,070 | 1,170 | 39,240 |
| 13 | 31,626 | 1,942 | 33,568 |
| 14 | 31,534 | 543 | 32,077 |
| 15 | 28,026 | 2,594 | 30,620 |
| TOTAL | 461,058 | 10,525 | 471,583 |

Consumption of Class III, GALS
Table L-1

(b) Discussion. The resupply options for maneuver units are: 1) resupply is unnecessary (Balance on Hand $\geq 75\%$ of Authorized); 2) standard resupply (Balance on Hand $\geq 50\%$ & $< 75\%$ of Authorized); or 3) emergency resupply (Balance on Hand $< 50\%$ of Authorized); reference Appendix B for definitions of "standard" and "emergency"

resupply. Table L-2 indicates during which TP(s) any maneuver unit(s) may have a BOH so low as to warrant the use of either standard or emergency resupply.

| RESUPPLY | TP | | | | | | | | | | | | | | | |
|------------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| RESUPPLY UNNEC | 87 | 87 | 87 | 87 | 84 | 85 | 85 | 84 | 84 | 83 | 84 | 82 | 80 | 81 | 76 | 80 |
| STANDARD RESUPPLY | 0 | 0 | 0 | 0 | 3 | 2 | 2 | 2 | 2 | 3 | 2 | 4 | 5 | 4 | 8 | 4 |
| EMERGENCY RESUPPLY | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 2 |
| ALL UNITS ¹ | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 87 | 86 | 86 |

¹ COMBAT INEFFECTIVE (DEAD) UNITS ARE NOT INCLUDED.

Number of Maneuver Units Needing Resupply, Class III
Table L-2

For more detail on individual units requiring resupply see table L-3 below. These units wait an average of 3.6 TPs (median of 2 TPs) before their BOH returns to a level no longer requiring resupply of class III.

| Unit | TP | | | | | | | | | | | | | | | | #TPs |
|---------|----|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|------|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
| B3001H2 | | | | | | | | | | | | 72 | | | | | 1 |
| B3002H2 | | | | | | | | | | | | | 74 | 68 | 65 | | 3 |
| B300AM2 | | | | | | | | | | | | | 74 | 72 | | | 2 |
| B300BM2 | | | | | | | | | | | | | | 75 | 70 | 65 | 3 |
| B3010RE | | | | | | | | | | | | | 73 | | | | 1 |
| B3013AR | | | | | | | | | | | | | | | 73 | | 1 |
| B3021MX | | | | | | | | | | | | | | | 74 | | 1 |
| B3023AR | | | | | | | | | | | | | | | 70 | 69 | 2 |
| B3031AR | | | | | | | | | | | | | | | 74 | | 1 |
| B3032AR | | | | | | | | | | | | | | | 74 | 59 | 2 |
| B3033MX | | | | | | | | | | | | | | 73 | 58 | | 2 |
| B000000 | | | | | 68 | 62 | 56 | 48 | 42 | 37 | 31 | 21 | 15 | 10 | 4 | 2 | 12 |
| B000CFC | | | | | 70 | 68 | 65 | 63 | 60 | 58 | 55 | 52 | 50 | 48 | 45 | 43 | 12 |
| B00A00H | | | | | 75 | | | | | 73 | 69 | 67 | 66 | | | 74 | 6 |
| B00E00H | | | | | | | | 50 | 59 | 54 | | 59 | 56 | | | | 5 |
| TOTAL | | | | | 3 | 2 | 2 | 3 | 3 | 4 | 3 | 5 | 7 | 6 | 10 | 6 | 54 |

Percentage of Balance On-Hand (%) for Maneuver Units
Requiring Resupply, Class III
Table L-3

For example, at the end of TP 11, B3001H2 had a class III BOH of 72%. This was the only TP in which B3001H2 could have asked for resupply. During TP 11, B3001H2 was one of 5 units capable of requesting resupply.

(c) Problems. Table L-3 shows BOH percentage for individual maneuver units requiring resupply. However, a review of individual orders revealed a problem with the availability of transporters (reference Table L-4).

| TP | REQUESTING UNIT | SUPPLY UNIT | SUPPLY TYPE | AMOUNT REQUESTED GALS | AMOUNT SHIPPED GALS | AMOUNT SHORTED (#) | TRUCKS AVAIL | AVAIL STOCKS GALS |
|----|-----------------|-------------|-------------|-----------------------|---------------------|--------------------|--------------|-------------------|
| 4 | B000CFC | B00RCSB | POL-BACFT | 9,306.48 | 1,124.71 | 87.9 | 0.0 | 114,754 |
| 4 | B000000 | B02RCSB | POL-BACFT | 9,231.16 | 1,124.71 | 87.8 | 0.0 | 115,875.3 |
| 4 | B000CFC | B00RCSB | POL-BACFT | 9,672.93 | 1,121.84 | 88.4 | 0.0 | 114,754 |
| 4 | B00A00H | B001CSA | POL-BACFT | 80,459.08 | 42,063.66 | 47.7 | 0.0 | 1,157,936.4 |
| 5 | B000CFC | B00RCSB | POL-BACFT | 9,977.57 | 1,118.98 | 88.8 | 0.0 | 112,518.4 |
| 5 | B000000 | B02RCSB | POL-BACFT | 11,628.5 | 1,120.41 | 90.4 | 0.0 | 114,754.9 |
| 5 | B000CFC | B00RCSB | POL-BACFT | 10,307.82 | 1,116.13 | 89.2 | 0.0 | 112,518.4 |
| 5 | B000000 | B02RCSB | POL-BACFT | 11,266.5 | 0 | 100.0 | 0.0 | 114,754.9 |
| 5 | B000CFC | B00RCSB | POL-BACFT | 9,948.57 | 0 | 100.0 | 0.0 | 112,518.4 |
| 6 | B000CFC | B00RCSB | POL-BACFT | 10,674.11 | 1,113.28 | 89.6 | 0.0 | 110,293.2 |
| 6 | B000000 | B02RCSB | POL-BACFT | 13,478 | 22.96 | 99.8 | 0.0 | 113,615.8 |
| 6 | B000CFC | B00RCSB | POL-BACFT | 11,013.31 | 1,111.86 | 89.9 | 0.0 | 110,293.2 |
| 6 | B000000 | B02RCSB | POL-BACFT | 14,178.45 | 1,116.13 | 92.1 | 0.0 | 113,615.8 |
| 6 | B000000 | B02RCSB | POL-BACFT | 13,779.2 | 0 | 100.0 | 0.0 | 113,615.8 |
| 7 | B000CFC | B00RCSB | POL-BACFT | 11,352.19 | 1,110.44 | 90.2 | 0.0 | 108,073.7 |
| 7 | B000CFC | B00RCSB | POL-BACFT | 10,980.64 | 0 | 100.0 | 0.0 | 108,073.7 |
| 7 | B000CFC | B00RCSB | POL-BACFT | 11,716.57 | 1,109.03 | 90.5 | 0.0 | 108,073.7 |
| 7 | B000000 | B02RCSB | POL-BACFT | 16,347.68 | 22.91 | 99.9 | 0.0 | 113,592.9 |
| 8 | B000CFC | B00RCSB | POL-BACFT | 12,057.62 | 1,107.61 | 90.8 | 0.0 | 105,859.9 |
| 8 | B000000 | B02RCSB | POL-BACFT | 16,990.36 | 1,113.28 | 93.4 | 0.0 | 112,479.6 |
| 8 | B000CFC | B00RCSB | POL-BACFT | 11,677.15 | 0 | 100.0 | 0.0 | 105,859.9 |
| 8 | B000CFC | B00RCSB | POL-BACFT | 12,401.38 | 1,106.2 | 91.1 | 0.0 | 105,859.9 |
| 8 | B000CFC | B00RCSB | POL-BACFT | 12,016.51 | 0 | 100.0 | 0.0 | 105,859.9 |
| 9 | B000CFC | B00RCSB | POL-BACFT | 12,734.96 | 1,104.79 | 91.3 | 0.0 | 103,653.2 |
| 9 | B000CFC | B00RCSB | POL-BACFT | 12,345.74 | 0 | 100.0 | 0.0 | 103,653.2 |
| 9 | B000000 | B02RCSB | POL-BACFT | 19,282.59 | 22.85 | 99.9 | 0.0 | 111,346.3 |
| 9 | B000CFC | B00RCSB | POL-BACFT | 13,058.45 | 1,101.97 | 91.6 | 0.0 | 103,653.2 |
| 9 | B000000 | B02RCSB | POL-BACFT | 19,900.34 | 1,110.44 | 94.4 | 0.0 | 111,346.3 |
| 9 | B00A00H | B001CSA | POL-BACFT | 71,949.36 | 41,739.51 | 42.0 | 0.0 | 1,099,546 |
| 9 | B000CFC | B00RCSB | POL-BACFT | 12,666.34 | 0 | 100.0 | 0.0 | 103,653.2 |
| 9 | B000000 | B02RCSB | POL-BACFT | 19,484.31 | 0 | 100.0 | 0.0 | 111,346.3 |
| 10 | B000CFC | B00RCSB | POL-BACFT | 13,373.35 | 1,097.76 | 91.8 | 0.0 | 101,461.9 |
| 10 | B000000 | B02RCSB | POL-BACFT | 20,167.1 | 0 | 100.0 | 0.0 | 110,217.4 |
| 10 | B000CFC | B00RCSB | POL-BACFT | 12,979.79 | 0 | 100.0 | 0.0 | 101,461.9 |
| 10 | B000000 | B02RCSB | POL-BACFT | 20,871.3 | 0 | 100.0 | 0.0 | 110,217.4 |
| 10 | B000CFC | B00RCSB | POL-BACFT | 13,681.16 | 1,093.56 | 92.0 | 0.0 | 101,461.9 |
| 10 | B000000 | B02RCSB | POL-BACFT | 21,559.25 | 22.76 | 99.9 | 0.0 | 110,217.4 |
| 10 | B000CFC | B00RCSB | POL-BACFT | 13,286.16 | 0 | 100.0 | 0.0 | 101,461.9 |
| 10 | B000000 | B02RCSB | POL-BACFT | 22,229.31 | 1,106.2 | 95.0 | 0.0 | 110,217.4 |
| 11 | B000CFC | B00RCSB | POL-BACFT | 13,981.93 | 1,089.39 | 92.2 | 0.0 | 99,287.3 |
| 11 | B000000 | B02RCSB | POL-BACFT | 21,793 | 0 | 100.0 | 0.0 | 110,194.7 |
| 11 | B00A00H | B001CSA | POL-BACFT | 91,940.84 | 0 | 100.0 | 0.0 | 1,042,499.4 |
| 11 | B000CFC | B00RCSB | POL-BACFT | 13,585.54 | 0 | 100.0 | 0.0 | 99,287.3 |
| 11 | B000000 | B02RCSB | POL-BACFT | 22,442.36 | 0 | 100.0 | 0.0 | 110,194.7 |
| 11 | B00A00H | B001CSA | POL-BACFT | 90,445.83 | 0 | 100.0 | 0.0 | 1,042,499.4 |
| 11 | B000CFC | B00RCSB | POL-BACFT | 14,267.56 | 1,085.22 | 92.4 | 0.0 | 99,287.3 |
| 11 | B000000 | B02RCSB | POL-BACFT | 23,109.79 | 0 | 100.0 | 0.0 | 110,194.7 |

| TP | REQUESTING UNIT | SUPPLY UNIT | SUPPLY TYPE | AMOUNT REQUESTED GALS | AMOUNT SHIPPED GALS | AMOUNT SHORTED (%) | TRUCKS AVAIL | AVAIL STOCKS GALS |
|----|-----------------|-------------|-------------|-----------------------|---------------------|--------------------|--------------|-------------------|
| 11 | B00A00H | B001CSA | POL-BACFT | 88,968.25 | 41,739.51 | 53.1 | 0.0 | 1,042,499.4 |
| 11 | B000CFC | B00RCSB | POL-BACFT | 13,869.79 | 0 | 100.0 | 0.0 | 99,287.3 |
| 11 | B000000 | B02RCSB | POL-BACFT | 23,763.25 | 22.67 | 99.9 | 0.0 | 110,194.7 |
| 11 | B000000 | B02RCSB | POL-BACFT | 23,931.75 | 0 | 100.0 | 0.0 | 110,194.7 |
| 12 | B000000 | B02RCSB | POL-BACFT | 24,098.92 | 1,106.2 | 95.4 | 0.0 | 109,088.5 |
| 12 | B000CFC | B00RCSB | POL-BACFT | 14,554.5 | 1,081.07 | 92.6 | 0.0 | 97,126.5 |
| 12 | B000000 | B02RCSB | POL-BACFT | 23,473.57 | 0 | 100.0 | 0.0 | 109,088.5 |
| 12 | B000CFC | B00RCSB | POL-BACFT | 14,155.39 | 0 | 100.0 | 0.0 | 97,126.5 |
| 12 | B000000 | B02RCSB | POL-BACFT | 24,324.33 | 0 | 100.0 | 0.0 | 109,088.5 |
| 12 | B000CFC | B00RCSB | POL-BACFT | 14,834.63 | 1,079.7 | 92.7 | 0.0 | 97,126.5 |
| 12 | B000000 | B02RCSB | POL-BACFT | 24,988.23 | 0 | 100.0 | 0.0 | 109,088.5 |
| 12 | B000CFC | B00RCSB | POL-BACFT | 14,431.46 | 0 | 100.0 | 0.0 | 97,126.5 |
| 13 | B000000 | B02RCSB | POL-BACFT | 25,595.17 | 22.67 | 99.9 | 0.0 | 107,959.6 |
| 13 | B000000 | B02RCSB | POL-BACFT | 25,701.11 | 1,106.2 | 95.7 | 0.0 | 107,959.6 |
| 13 | B000CFC | B00RCSB | POL-BACFT | 15,105.27 | 1,078.32 | 92.9 | 0.0 | 94,971.2 |
| 13 | B000CFC | B00RCSB | POL-BACFT | 14,698.08 | 0 | 100.0 | 0.0 | 94,971.2 |
| 13 | B000000 | B02RCSB | POL-BACFT | 25,917.6 | 0 | 100.0 | 0.0 | 107,959.6 |
| 13 | B000CFC | B00RCSB | POL-BACFT | 15,366.51 | 1,076.94 | 93.0 | 0.0 | 94,971.2 |
| 13 | B000000 | B02RCSB | POL-BACFT | 26,522.02 | 0 | 100.0 | 0.0 | 107,959.6 |
| 13 | B000CFC | B00RCSB | POL-BACFT | 14,955.33 | 0 | 100.0 | 0.0 | 94,971.2 |
| 14 | B000000 | B02RCSB | POL-BACFT | 27,120.69 | 0 | 100.0 | 0.0 | 106,830.8 |
| 14 | B000CFC | B00RCSB | POL-BACFT | 15,605.51 | 1,075.57 | 93.1 | 0.0 | 92,821.5 |
| 14 | B000000 | B02RCSB | POL-BACFT | 27,761.87 | 22.67 | 99.9 | 0.0 | 106,830.8 |
| 14 | B000CFC | B00RCSB | POL-BACFT | 15,190.39 | 0 | 100.0 | 0.0 | 92,821.5 |
| 14 | B000000 | B02RCSB | POL-BACFT | 27,901.48 | 1,106.2 | 96.0 | 0.0 | 106,830.8 |
| 14 | B000CFC | B00RCSB | POL-BACFT | 15,848.19 | 1,074.2 | 93.2 | 0.0 | 92,821.5 |
| 14 | B000CFC | B00RCSB | POL-BACFT | 15,429.17 | 0 | 100.0 | 0.0 | 92,821.5 |
| 15 | B000000 | B02RCSB | POL-BACFT | 28,069.75 | 0 | 100.0 | 0.0 | 105,701.9 |
| 15 | B000CFC | B00RCSB | POL-BACFT | 16,081.72 | 1,072.83 | 93.3 | 0.0 | 90,679.9 |
| 15 | B000000 | B02RCSB | POL-BACFT | 28,615.26 | 0 | 100.0 | 0.0 | 105,701.9 |
| 15 | B000CFC | B00RCSB | POL-BACFT | 15,658.83 | 0 | 100.0 | 0.0 | 90,679.9 |
| 15 | B000000 | B02RCSB | POL-BACFT | 28,996.32 | 0 | 100.0 | 0.0 | 105,701.9 |
| 15 | B000CFC | B00RCSB | POL-BACFT | 16,306.17 | 1,068.73 | 93.4 | 0.0 | 90,679.9 |
| 15 | B00A00H | B001CSA | POL-BACFT | 61,767.36 | 41,520.24 | 32.8 | 0.0 | 1,000,979.1 |
| 15 | B000000 | B02RCSB | POL-BACFT | 28,875.81 | 22.67 | 99.9 | 0.0 | 105,701.9 |
| 15 | B000000 | B02RCSB | POL-BACFT | 29,036.88 | 1,106.2 | 96.2 | 0.0 | 105,701.9 |
| 15 | B000CFC | B00RCSB | POL-BACFT | 15,882.2 | 0 | 100.0 | 0.0 | 90,679.9 |
| | TOTAL | | | 371,421.4 | 204,681.18 | 44.89 | | |

Problems Filling Maneuver Unit Orders, Class III
Table L-4

To quantify a measure of risk, the maximum consumption of class III by a unit for any TP is compared with the current BOH for each TP; if the value is less than one, the unit would exhaust its supplies prior to repeating the activities of this "maximum" TP. Where "at risk" is less than one TP of supply, class III was generally provided to maneuver units without placing them "at risk". Only one maneuver unit was "at risk". See Table L-5.

| | TP | | | | | | | | | | | | | | | | |
|---------------|----|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----------|
| MANEUVER UNIT | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | # of TPs |
| B000000 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 3 |

"At Risk" Units, Class III Risk
Table L-5

(d) Observation.

Class III CSS support was adequate and all maneuver units were supported in a "timely fashion"; however, there was a problem with the delivery of aircraft fuel due to the lack of available transporters.

(2) Supply Class V.

(a) Requirement. For the scenario, the requirement for class V (ammunition) was found by summing the consumption (quantities "used" plus quantities "lost") of all maneuver units (CSS units were excluded from this computation) during each of the 4-hour TPs. Calculated in "short tons (stons)," the requirement for class V for the length of the scenario is presented in table L-6.

| TP | USED STONS | LOST STONS | REQUIREMENT CONSUMED |
|-------|------------|------------|----------------------|
| 0 | 0 | 0 | 0 |
| 1 | 2,816 | 20 | 2,836 |
| 2 | 2,150 | 30 | 2,180 |
| 3 | 720 | 2 | 722 |
| 4 | 346 | 4 | 350 |
| 5 | 115 | 2 | 117 |
| 6 | 291 | 1 | 292 |
| 7 | 626 | 5 | 631 |
| 8 | 131 | 2 | 133 |
| 9 | 413 | 0 | 413 |
| 10 | 301 | 0 | 301 |
| 11 | 687 | 9 | 696 |
| 12 | 259 | 10 | 269 |
| 13 | 752 | 15 | 767 |
| 14 | 696 | 1 | 697 |
| 15 | 746 | 13 | 759 |
| TOTAL | 11,050 | 115 | 11,165 |

Consumption of Class V, STONS
Table L-6

(b) Discussion.

1) This analysis focuses on thirteen munition types {155MM, ATACMS, MLRS, Hellfire, Longbow, 2.75RKT, Patriot, Stinger, 120MM, 25MM, Javelin, LAW, and TOWII} using five indices {Amount Authorized, Amount On-Hand, Amount Used, Amount Lost, and Ratio of Amount On-Hand to Amount Authorized}. A list of all corps and division assets listing VIC unit name designators and their actual unit names is contained in Appendix A. A list of all supply analysis definitions is contained in Appendix B.

a) The thirteen aforementioned munition types were grouped into six functional categories (Field Artillery, Aviation, Air Defense Artillery, Armor & Mechanized Infantry, Anti-Armor, and Anti-Tank). Each of the functional categories was divided into subcategories displayed in table L-7:

| Category | Member Munition Type |
|-----------------------------|---|
| Field Artillery | 155MM - {M107 (CB), M116B1, M121A1, M449A1, M483A1, M549A1, M692/M731, M795, M825, M864, M864/AR, M864/GM, XM898, XM898/AR, XM898/GM, XM982, XM982/GM} ATACMS - {ATACMS-I, ATACMS-IA, ATACMS-II, ATACMS-IIA} MLRS - {ER-MLRS, ER-MLRS/GUIDED, M26, MSTAR} |
| Aviation | HELLFIRE, LONGBOW, 2.75RKT |
| Air Defense Artillery (ADA) | PATRIOT, STINGER |
| Armor & Mechanized Infantry | 120MM - {120MM, PGMM, M929, M933} |
| Anti-Armor | 25MM - {25MM, 40MM, 45MM} |
| Anti-Tank | JAVELIN, LAW, TOWII |

Key Functional Categories
Table L-7

b) Table L-8 displays the key munition types with the five aforementioned indices for each key munition at the end of the scenario. **The scenario end states shown are reliable indicators of individual unit supply status over the course of the scenario:**

c) Table L-8 represents an aggregation by munition type for all units in the modeled force. However, supply performance at some individual units for specific munitions varied significantly from these general indicators.

- The first column, key munition type, lists each of the munition types included for analysis in this report.

- The second column, amount authorized indicates quantities at initial state (TP 0) of the scenario.

- The total amount used of a key munition type (column three) can exceed the endstate BOH because during a particular TP a unit can receive a key munition type.

- Munitions lost due to combat activity (column four) did not cause any significant inventory imbalances resulting in availability shortfalls.

- The fifth and sixth columns, amount authorized and balance on hand (BOH) respectively, indicate quantities at endstate (TP 15) of the scenario.

- The seventh column, percentage of balance on hand of amount authorized, indicates that at endstate (TP 15) of the scenario, the quantity of munitions available for mission support was large and more than sufficient to meet requirements. **The Balance on Hand was at least one hundred percent of authorized for each munition type except (ATACMS and MLRS).**

| Key Munition Type | Initial State | Consumption | | Endstate | | |
|-------------------|-------------------------------|----------------------------|----------------------------|--------------------------------|---------------------|------------------------------|
| | Amt Authorized {Rounds} @ TP0 | Total Amount Used {Rounds} | Total Amount Lost {Rounds} | Amt Authorized {Rounds} @ TP15 | BOH @ TP15 {Rounds} | Percentage BOH of Authorized |
| 155MM | 61,146 | 42,469 | 834 | 41,063 | 42,779 | 104% |
| ATACMS | 432 | 83 | 0 | 363 | 351 | 97% |
| MLRS | 12,960 | 17,205 | 67 | 9,252 | 6,974 | 75% |
| HELLFIRE | 5,400 | 0 | 0 | 3,231 | 5,400 | 167% |

| Key Munition Type | Initial State | Consumption | | Endstate | | |
|-------------------|-------------------------------|----------------------------|----------------------------|--------------------------------|---------------------|------------------------------|
| | Amt Authorized {Rounds} @ TPO | Total Amount Used {Rounds} | Total Amount Lost {Rounds} | Amt Authorized {Rounds} @ TP15 | BOH @ TP15 {Rounds} | Percentage BOH of Authorized |
| Longbow | 5,400 | 1 | 0 | 3,454 | 5,417 | 157% |
| 2.75RKT | 27,360 | 8 | 0 | 16,274 | 27,345 | 168% |
| Patriot | 128 | 0 | 0 | 8 | 128 | 1,600% |
| Stinger | 2,024 | 0 | 5 | 1,548 | 2,901 | 187% |
| 120MM | 13,240 | 2,267 | 235 | 7,515 | 23,230 | 309% |
| 25MM | 362,340 | 194 | 17,819 | 221,047 | 590,313 | 267% |
| Javelin | 1,170 | 28 | 16 | 977 | 1,109 | 114% |
| LAW | 1,527 | 7 | 22 | 1,376 | 3,025 | 220% |
| TOWII | 2,652 | 9 | 63 | 1,492 | 5,160 | 346% |

Key Munition Status
Table L-8

d) Table L-9 provides an overall summary of the additional supply indicators which help assess the sufficiency of munition availability. Although the indicators are shown by munition type, the individual indicators represent the presence (Yes) or absence (No) of that indicator for some specific unit(s) in the force at the end of a specific TP. Tables L-10 thru L-19 provide more detailed analyses of the aforementioned munition availability criteria.

| Key Munition Type | BOH(>=75%) | Standard Replenishment BOH(50%-74%) | Emergency Replenishment BOH(1%-49%) | BOH(=0) |
|-------------------|------------|-------------------------------------|-------------------------------------|---------|
| 155MM | Yes | Yes | Yes | Yes |
| ATACMS | Yes | Yes | No | No |
| MLRS | Yes | Yes | Yes | Yes |
| HELLFIRE | Yes | No | No | No |
| Longbow | Yes | Yes | No | No |
| 2.75RKT | Yes | No | No | No |
| Patriot | Yes | No | No | No |
| Stinger | Yes | Yes | No | No |
| 120MM | Yes | No | Yes | No |
| 25MM | Yes | No | No | No |
| Javelin | Yes | No | No | No |
| LAW | Yes | No | No | No |
| TOWII | Yes | No | No | No |

Balance on Hand Status
Table L-9

- Balance on Hand (>=75%) of Authorized: Initially all units start in this range since the amount authorized is equal to the balance on hand. BOHs which remain in this range maintain a sufficient quantity of authorized munitions and at no time throughout the scenario require supply replenishment.

- Balance on Hand (50%-74%) of Authorized: This column indicates whether or not the BOH by munition type at any unit fell to the indicated percentage range of the authorized amount. BOH in this range triggers "standard supply replenishment" requests.

-- For eight of the munition types (HELLFIRE, 2.75RKT, PATRIOT, 120MM, 25MM, JAVELIN, LAW, and TOWII) no standard supply replenishment was required at any time during the scenario. No HELLFIRE, PATRIOT, or STINGER munition type was expended during

this scenario. Also, no ATACMS, HELLFIRE, LONGBOW, 2.75RKT or PATRIOT munition type was lost due to attrition of systems.

-- The other five munition types (155MM, ATACMS, MLRS, LONGBOW, and STINGER) triggered standard resupply orders at some specific unit. Tables L-10 through L-14 identify the unit, the time period, and the sub-munition(s) which triggered a standard resupply order.

| Unit Name | BOH(50%-74%) | Time Period(TP) | Sub-munition |
|-----------------------------------|--------------|-----------------|--------------|
| 3RD BN 63TH FA BDE (155 SP) | 72% | TP 0 | M107(CB) |
| | 57% | TP 2 | M107(CB) |
| | 59% | TP 3 | M107(CB) |
| | 68% | TP 5 | M549A1 |
| | 62% | TP 7 & 8 | M795 |
| | 63% | TP 9 | M107(CB) |
| | 64% | TP 10 | M107(CB) |
| | 55% | TP 10 | XM898 |
| | 65% | TP 11 | M107(CB) |
| | 66% | TP 12 | M107(CB) |
| | 50% | TP 12 | M549A1 |
| | 61% | TP 15 | M107(CB) |
| 4TH BN 63TH FA BDE (155 SP) | 72% | TP 0 & 11 | M107(CB) |
| | 74% | TP 1 | M107(CB) |
| | 53% | TP 2 & 3 | M107(CB) |
| | 51% | TP 6 | M549A1 |
| | 56% | TP 7 | M107(CB) |
| | 59% | TP 8 | M107(CB) |
| | 60% | TP 9 | M107(CB) |
| | 61% | TP 10 | M107(CB) |
| | 73% | TP 12 | M107(CB) |
| 3RD BN 65TH FA BDE (MLRS) | 72% | TP 0 | M107(CB) |
| | 53% | TP 13 | M107(CB) |
| | 54% | TP 14 | M107(CB) |
| | 55% | TP 15 | M107(CB) |
| | 54% | TP 15 | M107(CB) |
| A BTRY 1ST BN 67TH FA BDE (155 T) | 53% | TP 2 | M795 |
| | 74% | TP 9 | M795 |
| B BTRY 1ST BN 67TH FA BDE (155 T) | 51% | TP 1 & 2 | M795 |
| A BTRY 2ND BN 67TH FA BDE (155 T) | 50% | TP 2 | M795 |
| B BTRY 2ND BN 67TH FA BDE (155 T) | 50% | TP 2 | M795 |
| | 62% | TP 3 | M795 |
| | 65% | TP 4 | M795 |
| | 69% | TP 5 | M795 |
| | 74% | TP 6 | M795 |
| C BTRY 2ND BN 67TH FA BDE (155 T) | 50% | TP 2 | M795 |
| | 53% | TP 3 | M795 |
| A BTRY 3RD BN 67TH FA BDE (155 T) | 50% | TP 2 | M795 |
| | 53% | TP 3 | M795 |
| B BTRY 3RD BN 67TH FA BDE (155 T) | 50% | TP 2 | M795 |
| | 53% | TP 3 | M795 |
| C BTRY 3RD BN 67TH FA BDE (155 T) | 50% | TP 2 | M795 |
| | 53% | TP 3 | M795 |
| 1ST BN 3D FA (155 SP) | 72% | TP 0 | M107(CB) |
| | 55% | TP 13 | M864 |
| | 56% | TP 14 | M864 |
| | 57% | TP 15 | M864 |
| 2ND BN 3D FA (155 SP) | 72% | TP 0 | M107(CB) |
| 3RD BN 3D FA (155 SP) | 72% | TP 0 | M107(CB) |

155MM Standard Replenishment
Table L-10

| Unit Name | BOH(50%-74%) | Time Period(TP) | Sub-munition |
|-----------|--------------|-----------------|--------------|
|-----------|--------------|-----------------|--------------|

| | | | |
|---------------------------|-----|------------|----------|
| 1ST BN 69TH FA BDE (MLRS) | 71% | TP 3 | ATACMS_I |
| | 66% | TP 4 | ATACMS_I |
| | 67% | TP 5,6,7 | ATACMS_I |
| | 68% | TP 8 & 10 | ATACMS_I |
| | 69% | TP 9 | ATACMS_I |
| | 61% | TP 11 & 12 | ATACMS_I |
| | 62% | TP 13 | ATACMS_I |
| | 63% | TP 14 & 15 | ATACMS_I |

ATACMS Standard Replenishment
Table-11

| Unit Name | BOH(50%-74%) | Time Period(TP) | Sub-munition |
|---------------------------|--------------|-----------------|---------------|
| 1ST BN 63TH FA BDE (MLRS) | 70% | TP 2 | ER-MLRS |
| | 53% | TP 13 | M26 |
| 2ND BN 63TH FA BDE (MLRS) | 70% | TP 2 | ER-MLRS |
| | 52% | TP 2 | M26 |
| | 50% | TP 2 | MSTAR |
| | 63% | TP 12 | MSTAR |
| 1ST BN 65TH FA BDE (MLRS) | 51% | TP 1 | ER-MLRS |
| | 53% | TP 7 | ER-MLRS |
| | 61% | TP 7 | M26 |
| | 54% | TP 8 | ER-MLRS |
| | 56% | TP 8 | M26 |
| | 55% | TP 9 | ER-MLRS |
| 2ND BN 65TH FA BDE (MLRS) | 66% | TP 1 | ER-MLRS |
| | 59% | TP 6 | MSTAR |
| | 66% | TP 8 | MSTAR |
| | 60% | TP 9 | M26 |
| 2ND BN 69TH FA BDE (MLRS) | 73% | TP 5 | M26 |
| | 69% | TP 11 | MSTAR |
| 3RD BN 69TH FA BDE (MLRS) | 67% | TP 1 | MSTAR |
| | 65% | TP 8 & 9 | M26 |
| A BTRY 3D FA (MLRS) | 58% | TP 13 | MSTAR |
| | 68% | TP 13 | M26 |
| | 62% | TP 14 & 15 | ER-MLRS/GUIDE |
| B BTRY 3D FA (MLRS) | 50% | TP 13 | ER-MLRS/GUIDE |

MLRS Standard Replenishment
Table L-12

| Unit Name | BOH(50%-74%) | Time Period(TP) | Sub-munition |
|--------------------------|--------------|-----------------|--------------|
| 1ST BN 102ND ATK HEL RGT | 57% | TP 8 | Longbow |

Longbow Standard Replenishment
Table-13

| Unit Name | BOH(50%-74%) | Time Period(TP) | Sub-munition |
|--------------------------|--------------|-----------------|--------------|
| 1ST BN 102ND ATK HEL RGT | 72% | TP 8 | STINGER |

STINGER Standard Replenishment
Table-14

- Balance on Hand (1%-49%) of Authorized: This column indicates whether or not the BOH by munition type at any unit fell to the indicated percentage range of the authorized amount. BOH in this range triggers "emergency supply replenishment" requests. Three of the munition types (155MM, MLRS, and 120MM) required emergency resupply. Tables L-15 through L-17 depict specific unit, time period, and sub-munition type which generate an emergency resupply request.

| Unit Name | BOH(1%-49%) | Time Period(TP) | Sub-munition |
|-----------|-------------|-----------------|--------------|
|-----------|-------------|-----------------|--------------|

| Unit Name | BGH(1%-49%) | Time Period(TP) | Sub-munition |
|-----------------------------------|-------------|-----------------|--------------|
| 3RD BN 63TH FA BDE (155 SP) | 20% | TP 1 | M549A1 |
| | 35% | TP 1 | M864 |
| | 16% | TP 1 | XM982 |
| | 23% | TP 2 & 3 | M549A1 |
| | 37% | TP 2 & 3 | M795 |
| | 46% | TP 4 | M549A1 |
| | 38% | TP 4 | M795 |
| | 3% | TP 4 - 8 | XM898 |
| | 39% | TP 6 | M795 |
| | 4% | TP 7 | XM982 |
| | 41% | TP 9 | XM898 |
| | 30% | TP 9 | M795 |
| | 31% | TP 10 & 11 | M795 |
| | 5% | TP 10,11,12 | XM982 |
| | 30% | TP 11 | XM898 |
| | 50% | TP 11 | M549A1 |
| | 30% | TP 11 | M483A1 |
| | 31% | TP 12 & 13 | M483A1 |
| | 31% | TP 12 & 13 | XM898 |
| | 32% | TP 12 | M795 |
| | 6% | TP 13 | M795 |
| | 24% | TP 14 | M107 (CB) |
| | 32% | TP 14 | XM898 |
| | 5% | TP 14 | XM982 |
| 4TH BN 63TH FA BDE (155 SP) | 20% | TP 1 | M549A1 |
| | 22% | TP 2,3,4,5 | M549A1 |
| | 35% | TP 2 & 3 | M795 |
| | 36% | TP 4 & 5 | M795 |
| | 37% | TP 6 | M795 |
| | 2% | TP 7 & 8 | M795 |
| | 3% | TP 9 - 15 | M864 |
| | 28% | TP 10 | M483A1 |
| | 29% | TP 10 | XM982 |
| | 32% | TP 11 & 12 | XM982 |
| | 42% | TP 11 | M795 |
| | 43% | TP 12 & 13 | M795 |
| | 25% | TP 13 | M107 (CB) |
| | 33% | TP 13 & 14 | XM982 |
| | 26% | TP 14 | M107 (CB) |
| | 39% | TP 14 | M483A1 |
| | 34% | TP 15 | XM982 |
| 1ST BN 65TH FA BDE (MLRS) | 48% | TP 1 | M107 (CB) |
| | 32% | TP 1 | M795 |
| | 21% | TP 1 | M549A1 |
| | 22% | TP 2 & 3 | M549A1 |
| | 33% | TP 2 | M795 |
| | 49% | TP 2 | M107 (CB) |
| | 34% | TP 3 | M795 |
| | 23% | TP 4 | M549A1 |
| | 35% | TP 4 | M795 |
| | 36% | TP 5 & 6 | M795 |
| | 10% | TP 5 | XM898 |
| | 45% | TP 7 | M549A1 |
| | 3% | TP 7,8,9,11,13 | M795 |
| | 31% | TP 8 | M549A1 |
| | 4% | TP 8,9,11 | XM898 |
| | 24% | TP 9,10,11,12 | M549A1 |
| | 1% | TP 13 & 14 | M549A1 |
| | 24% | TP 13 | M483A1 |
| A BTRY 1ST BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 49% | TP 1 | M795 |
| | 36% | TP 1 | M864/AR |
| | 36% | TP 1 | M864/GM |
| | 23% | TP 2 | M116B1 |
| | 39% | TP 2 | M864/AR |
| | 39% | TP 2 | M864/GM |
| | 34% | TP 14 | M795 |

| Unit Name | BQM(1% - 49%) | Time Period(TP) | Sub-munition |
|-----------------------------------|---------------|-----------------|--------------|
| B BTRY 1ST BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 22% | TP 1 & 2 | M116B1 |
| | 37% | TP 1 & 2 | M864/AR |
| | 37% | TP 1 & 2 | M864/GM |
| | 33% | TP 13 | M107 (CB) |
| | 38% | TP 13 | M795 |
| C BTRY 1ST BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 48% | TP 1 | M795 |
| | 35% | TP 1 | M864/AR |
| | 35% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 50% | TP 2 | M795 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| | 37% | TP 13 | M795 |
| | | | |
| A BTRY 2ND 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 47% | TP 1 | M795 |
| | 34% | TP 1 | M864/AR |
| | 34% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| B BTRY 2ND 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 47% | TP 1 | M795 |
| | 34% | TP 1 | M864/AR |
| | 34% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| | 13% | TP 13 | M107 (CB) |
| | 14% | TP 14 | M107 (CB) |
| | 15% | TP 15 | M107 (CB) |
| C BTRY 2ND BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 47% | TP 1 | M795 |
| | 34% | TP 1 | M864/AR |
| | 34% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| | 23% | TP 3 | M116B1 |
| | 39% | TP 3 | M864/AR |
| | 39% | TP 3 | M864/GM |

| Unit Name | BOH(14-49%) | Time Period(TP) | Sub-munition |
|-----------------------------------|-------------|-----------------|--------------|
| A BTRY 3RD BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 47% | TP 1 | M795 |
| | 34% | TP 1 | M864/AR |
| | 34% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| | 23% | TP 3 | M116B1 |
| | 39% | TP 3 | M864/AR |
| | 39% | TP 3 | M864/GM |
| B BTRY 3RD BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 47% | TP 1 | M795 |
| | 34% | TP 1 | M864/AR |
| | 34% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| | 23% | TP 3 | M116B1 |
| | 39% | TP 3 | M864/AR |
| | 39% | TP 3 | M864/GM |
| C BTRY 3RD BN 67TH FA BDE (155 T) | 20% | TP 0 | M116B1 |
| | 46% | TP 0 | M795 |
| | 33% | TP 0 | M864/AR |
| | 33% | TP 0 | M864/GM |
| | 21% | TP 1 | M116B1 |
| | 47% | TP 1 | M795 |
| | 34% | TP 1 | M864/AR |
| | 34% | TP 1 | M864/GM |
| | 22% | TP 2 | M116B1 |
| | 36% | TP 2 | M864/AR |
| | 36% | TP 2 | M864/GM |
| | 23% | TP 3 | M116B1 |
| | 39% | TP 3 | M864/AR |
| | 39% | TP 3 | M864/GM |
| 1ST BN 3D FA (155 SP) | 40% | TP 11 | M864 |
| | 41% | TP 12 | M864 |
| 2ND BN 3RD FA (155 SP) | 39% | TP 11 & 12 | M795 |
| | 29% | TP 12 | M483A1 |
| 3RD BN 3RD FA (155 SP) | 36% | TP 12 | M795 |
| | 22% | TP 12 | M549A1 |

155MM Emergency Replenishment
Table L-15

| Unit Name | BOH(14-49%) | Time Period(TP) | Sub-munition |
|---------------------------|-------------|-----------------|--------------|
| 1ST BN 63TH FA BDE (MLRS) | 17% | TP 2 | M26 |
| | 42% | TP 2 | MSTAR |
| | 19% | TP 9 | MSTAR |
| | 20% | TP 10 | MSTAR |
| | 22% | TP 11 | MSTAR |
| | 13% | TP 14 | M26 |
| 2ND BN 63TH FA BDE (MLRS) | 4% | TP 3 | MSTAR |
| | 31% | TP 10 | ER-MLRS |
| | 24% | TP 10 | M26 |
| | 43% | TP 10 | MSTAR |
| | 22% | TP 11 | MSTAR |
| 1ST BN 65TH FA BDE (MLRS) | 6% | TP 1 | M26 |
| | 22% | TP 1 | MSTAR |
| | 24% | TP 6 | MSTAR |
| | 19% | TP 9 | M26 |

| Unit Name | BOH (1%-49%) | Time Period (TP) | Sub-munition |
|---------------------------|--------------|------------------|--------------|
| 2ND BN 65TH FA BDE (MLRS) | 26% | TP 1 | MSTAR |
| | 31% | TP 5 | M26 |
| | 38% | TP 5 | MSTAR |
| | 38% | TP 6 | M26 |
| | 40% | TP 7 | MSTAR |
| | 36% | TP 8 | ER-MLRS |
| | 10% | TP 9 | ER-MLRS |
| 2ND BN 69TH FA BDE (MLRS) | 43% | TP 10 | M26 |
| | 29% | TP 1 | M26 |
| | 7% | TP 2 | ER-MLRS |
| | 45% | TP 2 | MSTAR |
| | 22% | TP 3 | MSTAR |
| | 20% | TP 6 | M26 |
| | 31% | TP 8 | MSTAR |
| 3RD BN 69TH FA BDE (MLRS) | 32% | TP 9 | MSTAR |
| | 26% | TP 1 | M26 |
| | 27% | TP 2 | ER-MLRS |
| | 13% | TP 2 | M26 |
| | 9% | TP 2 | MSTAR |
| | 10% | TP 3 | MSTAR |
| | 33% | TP 6 & 8 | MSTAR |
| | 32% | TP 7 | MSTAR |
| A BTRY 3D FA (MLRS) | 26% | TP 9 | MSTAR |
| | 22% | TP 12 | ER-MLRS |
| | 46% | TP 13 | ER-MLRS |
| B BTRY 3D FA (MLRS) | 39% | TP 14 | M26 |
| | 39% | TP 14 | ER-MLRS |
| | 17% | TP 14 | M26 |

MLRS Emergency Replenishment
Table L-16

| Unit Name | BOH (1%-49%) | Time Period (TP) | Sub-munition |
|-------------------|--------------|------------------|--------------|
| B TRP 3D CAV SQDN | 37% | TP 13 | M933 |
| C TRP 3D CAV SQDN | 35% | TP 12 | M933 |
| | 36% | TP 13 | M933 |
| TF 1-78 MECH | 29% | TP 14 | M933 |
| | 30% | TP 15 | M933 |
| TF 1-79 MECH | 29% | TP 14 | M933 |
| | 31% | TP 15 | M933 |
| TF 1-3 AR | 30% | TP 15 | M933 |

120MM Emergency Replenishment
Table L-17

- Zero Balance on Hand: This column indicates whether or not the BOH by munition type at any unit fell to zero. Two of the munition types (155MM and MLRS) experience a zero balance on hand. Tables L-18 and L-19 depict specific unit, time period, and sub-munition type which experience a zero balance on hand.

| Unit Name | BOH (-0) | Time Period (TP) | Sub-munition |
|-----------------------------|----------|--------------------|--------------|
| 3RD BN 63TH FA BDE (155 SP) | 0% | TP 2 - 15 | M449A1 |
| | 0% | TP 2 - 10 | M483A1 |
| | 0% | TP 2 - 15 | M864 |
| | 0% | TP 2 & 3 | XM898 |
| | 0% | TP 2 - 6,8,9,13,15 | XM982 |
| | 0% | TP 7,8,14 | M795 |
| | 0% | TP 13,14,15 | M549A1 |
| 4TH BN 63TH FA BDE (155 SP) | 0% | TP 2 -15 | M449A1 |
| | 0% | TP 2 - 6,8,9 | M483A1 |
| | 0% | TP 11,12,13 | M483A1 |
| | 0% | TP 2 - 8 | M864 |
| | 0% | TP 2 - 9 | XM898 |
| | 0% | TP 2 - 9 | XM982 |
| | 0% | TP 9,14,15 | M795 |

| Unit Name | BOP(=0) | Time Period(TP) | Sub-munition |
|-----------------------------------|---------|--------------------|--------------|
| 1ST BN 65TH FA BDE (MLRS) | 0% | TP 1 - 15 | M449A1 |
| | 0% | TP 1 - 7,12 | M483A1 |
| | 0% | TP 1,2,4 - 15 | M864 |
| | 0% | TP 1 - 4,5,6 | XM898 |
| | 0% | TP 10,11 - 15 | XM898 |
| | 0% | TP 1 - 15 | XM892 |
| | 0% | TP 10,12,14,15 | M795 |
| | 0% | TP 15 | M549A12 |
| A BTRY 1ST BN 67TH FA BDE (155 T) | 0% | TP 1,2,3,5 - 15 | M864 |
| | 0% | TP 1,2,14,15 | M483A1 |
| | 0% | TP 4 - 11,14,15 | XM982 |
| | 0% | TP 12 - 15 | M549A1 |
| | 0% | TP 12 - 15 | XM898 |
| | 0% | TP 13,14,15 | M107(CB) |
| | 0% | TP 13 & 15 | M795 |
| | 0% | TP 14 & 15 | M449A1 |
| B BTRY 1ST BN 67TH FA BDE (155 T) | 0% | TP 1 & 2 | M483A1 |
| | 0% | TP 4 - 11,13,14,15 | XM982 |
| | 0% | TP 5 - 15 | M864 |
| | 0% | TP 12 - 15 | M549A1 |
| | 0% | TP 14 & 15 | M107(CB) |
| | 0% | TP 14 & 15 | M795 |
| | 0% | TP 15 | M449A1 |
| | 0% | TP 15 | M449A1 |
| C BTRY 1ST BN 67TH FA BDE (155 T) | 0% | TP 1 & 2 | M483A1 |
| | 0% | TP 4 - 11,13,14,15 | XM982 |
| | 0% | TP 5 - 15 | M864 |
| | 0% | TP 12 - 15 | M549A1 |
| | 0% | TP 14 & 15 | M107(CB) |
| | 0% | TP 14 & 15 | M795 |
| | 0% | TP 15 | M449A1 |
| | 0% | TP 15 | M449A1 |
| A BTRY 2ND BN 67TH FA BDE (155 T) | 0% | TP 4 - 11,14,15 | XM982 |
| | 0% | TP 11 - 15 | M864 |
| | 0% | TP 12 - 15 | M549A1 |
| | 0% | TP 12 - 15 | M795 |
| | 0% | TP 13,14,15 | M107(CB) |
| | 0% | TP 15 | M449A1 |
| B BTRY 2ND BN 67TH FA BDE (155 T) | 0% | TP 4 - 11,15 | XM982 |
| | 0% | TP 11 - 15 | M795 |
| | 0% | TP 12 - 15 | M864 |
| | 0% | TP 12 - 15 | M549A1 |
| | 0% | TP 15 | M449A1 |
| | 0% | TP 15 | M449A1 |
| C BTRY 2ND BN 67TH FA BDE (155 T) | 0% | TP 4 - 11,14,15 | XM982 |
| | 0% | TP 11 - 15 | M549A1 |
| | 0% | TP 12 - 15 | M795 |
| | 0% | TP 12 - 15 | M864 |
| | 0% | TP 14,15 | M449A1 |
| | 0% | TP 15 | M449A1 |
| A BTRY 3RD BN 67TH FA BDE (155 T) | 0% | TP 4 - 12 | XM982 |
| B BTRY 3RD BN 67TH FA BDE (155 T) | 0% | TP 4 - 12 | XM982 |
| C BTRY 3RD BN 67TH FA BDE (155 T) | 0% | TP 4 - 12 | XM982 |
| 2ND BN 3D FA (155 SP) | 0% | TP 14 & 15 | M449A1 |
| 3RD BN 3D FA (155 SP) | 0% | TP 15 | M864 |
| | 0% | TP 15 | XM982 |

155MM Zero Balance
Table L-18

| Unit Name | BOP(=0) | Time Period(TP) | Sub-munition |
|---------------------------|---------|-------------------|--------------|
| 1ST BN 63TH FA BDE (MLRS) | 0% | TP 3 - 15 | ER-MLRS |
| | 0% | TP 3 - 12 | M26 |
| | 0% | TP 3 - 8 | MSTAR |
| 2ND BN 63TH FA BDE (MLRS) | 0% | TP 3 - 9,11 - 15 | ER-MLRS |
| | 0% | TP 3 - 9,11 | M26 |
| | 0% | TP 4 - 9 | MSTAR |
| 1ST BN 65TH FA BDE (MLRS) | 0% | TP 4 - 6,12 - 15 | ER-MLRS |
| | 0% | TP 4 - 12,10 - 14 | M26 |
| | 0% | TP 5 - 10 | MSTAR |

| Unit Name | BOH(+0) | Time Period(TP) | Sub-munition |
|---------------------------|----------------|--|-------------------------|
| 2ND BN 65TH FA BDE (MLRS) | 0% 0% 0% | TP 1 - 4,7,10 - 14 TP 2 - 8,12 - 15 TP 2,3,4 | M26 ER-MLRS MSTAR |
| 2ND BN 69TH FA BDE (MLRS) | 0% 0% 0% | TP 2,3,4,7 - 10 TP 3 - 8,10 - 15 TP 4 - 7 | M26 ER-MLRS MSTAR |
| 3RD BN 69TH FA BDE (MLRS) | 0% 0% 0% | TP 3 - 9,13,14,15 TP 3,4,5 TP 4 & 5 | ER-MLRS M26 MSTAR |
| A BTRY 3D FA (MLRS) | 0% | TP 15 | M26 |
| B BTRY 3D FA (MLRS) | 0% | TP 15 | M26 |

MLRS Zero Balance
Table L-19

(c) Problems. Of the 10,244 stons ordered, via standard resupply, 8,262 stons were shipped (approximately 80.65 percent). Problems in unfilled orders are associated with unavailable transporters or replenishments (reference table L-20).

| TP | REQUESTING UNIT | SUPPLY UNIT | SUPPLY TYPE | AMOUNT REQUESTED (Rounds) | AMOUNT SHIPPED (Rounds) | AMOUNT SHORTED (%) | TRUCKS AVAIL | AVAIL STOCKS (Rounds) |
|----|-----------------|-------------|-------------|---------------------------|-------------------------|--------------------|--------------|-----------------------|
| 1 | B3001H2 | B301ATP | M107 (CB) | 481.59 | 430 | 10.7 | 17.6 | 0 |
| 1 | B3003H2 | B303ATP | M107 (CB) | 481.59 | 30 | 93.8 | 17.8 | 0 |
| 1 | B00C3H2 | B001ASP | M483A1 | 864.43 | 144.43 | 83.3 | 0.0 | 152,882.6 |
| 1 | B00C3H2 | B001ASP | M795 | 335.59 | 0 | 100.0 | 0.0 | 6,802.3 |
| 1 | B00C3H2 | B001ASP | M449A1 | 171.47 | 0 | 100.0 | 0.0 | 17,136 |
| 2 | B00C3H2 | B001ASP | M483A1 | 2,193.01 | 0.12 | 100.0 | 0.0 | 151,910 |
| 2 | B00A4H2 | B001ASP | XM982 | 216.59 | 52.94 | 75.6 | 0.0 | 700.8 |
| 2 | B00E00H | B001ASP | Longbow | 962.83 | 100 | 89.6 | 2.0 | 0 |
| 2 | B00A3H2 | B001ASP | M483A1 | 1,096.15 | 498.29 | 54.5 | 0.0 | 151,910 |
| 2 | B00A3H2 | B001ASP | XM898 | 85.18 | 0 | 100.0 | 0.0 | 1,701.2 |
| 3 | B00G3M2 | B001ASP | ER-MLRS | 435.17 | 286.03 | 34.3 | 14.8 | 0 |
| 3 | B00C3H2 | B001ASP | M483A1 | 2,130.77 | 736.84 | 65.4 | 0.0 | 151,173.2 |
| 3 | B00C3H2 | B001ASP | M795 | 314.29 | 0 | 100.0 | 0.0 | 6,090.6 |
| 3 | B00C3H2 | B001ASP | M449A1 | 216.33 | 0 | 100.0 | 0.0 | 17,136 |
| 4 | B00A4H2 | B001ASP | M483A1 | 1,734.45 | 480.83 | | 0.0 | 149,352.5 |
| 4 | B00A3H2 | B001ASP | M483A1 | 1,530.58 | 882.66 | 42.3 | 0.0 | 149,352.5 |
| 4 | B00C3H2 | B001ASP | M483A1 | 1,811.08 | 457.2 | 74.8 | 0.0 | 149,352.5 |
| 5 | B00C3H2 | B001ASP | M795 | 283.68 | 3.16 | 98.9 | 0.0 | 6,087.5 |
| 5 | B00A3H2 | B001ASP | M483A1 | 1,520.26 | 176.65 | 88.4 | 0.0 | 147,316.4 |
| 5 | B00A3H2 | B001ASP | XM898 | 257.08 | 0 | 100.0 | 0.0 | 1,367.7 |
| 5 | B00A4H2 | B001ASP | M483A1 | 1,711.1 | 57.51 | 96.6 | 0.0 | 147,316.4 |
| 5 | B00A4H2 | B001ASP | XM898 | 301.1 | 0 | 100.0 | 0.0 | 1,367.7 |
| 5 | B00A4H2 | B001ASP | XM982 | 182.1 | 0 | 100.0 | 0.0 | 580.4 |
| 6 | B00C3H2 | B001ASP | M795 | 273.71 | 143.75 | 47.5 | 0.0 | 5,943.7 |
| 6 | B00A4H2 | B001ASP | M483A1 | 1,682.52 | 251.03 | 85.1 | 0.0 | 147,065.4 |
| 7 | B00A4H2 | B001ASP | M483A1 | 1,669.84 | 96.19 | 94.2 | 0.0 | 146,969.2 |
| 7 | B00A3H2 | B001ASP | XM982 | 174.84 | 69.51 | 60.2 | 0.0 | 289 |
| 8 | B00A4H2 | B001ASP | M483A1 | 1,638.13 | 322.7 | 80.3 | 0.0 | 146,646.5 |
| 8 | B00A4H2 | B001ASP | M864 | 184.25 | 0 | 100.0 | 0.0 | 3,113.1 |
| 8 | B00C3H2 | B001ASP | M549A1 | 568.61 | 0.12 | 100.0 | 0.0 | 24,285.1 |
| 8 | B00C3H2 | B001ASP | M795 | 268.29 | 0 | 100.0 | 0.0 | 5,943.7 |
| 10 | B00C2M2 | B001ASP | M26 | 345.83 | 136.09 | 60.6 | 45.6 | 0 |

| TP | REQUESTING UNIT | SUPPLY UNIT | SUPPLY TYPE | AMOUNT REQUESTED (Rounds) | AMOUNT SHIPPED (Rounds) | AMOUNT SHORTED (%) | TRUCKS AVAIL | AVAIL STOCKS (Rounds) |
|----|-----------------|-------------|-------------|---------------------------|-------------------------|--------------------|--------------|-----------------------|
| 11 | B00A4H2 | B001ASP | M483A1 | 1,241.76 | 651.19 | 47.6 | 0.0 | 145,995.3 |
| 11 | B00A4H2 | B001ASP | M795 | 175.13 | 0 | 100.0 | 0.0 | 5,650.1 |
| 11 | B00A3H2 | B001ASP | M549A1 | 140.6 | 0 | 100.0 | 0.0 | 23,899.6 |
| 11 | B3001H2 | B301ATP | M864 | 126.72 | 25 | 80.3 | 13.6 | 0 |
| 11 | B00A3H2 | B001ASP | M549A1 | 378.54 | 0 | 100.0 | 0.0 | 23,899.6 |
| 13 | B00C3H2 | B001ASP | M549A1 | 588.03 | 249.63 | 57.5 | 0.0 | 23,609.9 |
| 13 | B00C3H2 | B001ASP | M795 | 249.71 | 0 | 100.0 | 0.0 | 5,500.9 |
| 13 | B00A3H2 | B001ASP | M107 (CB) | 389.81 | 117.29 | 69.9 | 0.0 | 13,403.2 |
| 14 | B00C3H2 | B001ASP | M549A1 | 645.56 | 457.2 | 29.2 | 0.0 | 22,782.3 |
| 14 | B00A3H2 | B001ASP | M549A1 | 617.34 | 194.62 | 68.5 | 0.0 | 22,782.3 |
| 14 | B00A3H2 | B001ASP | M549A1 | 614.02 | 175.82 | 71.4 | 0.0 | 22,782.3 |
| 15 | B3001H2 | B301ATP | M864 | 81.58 | 24.69 | 69.7 | 11.7 | 0 |
| | TOTAL | | | 31,371.2 | 7,251.49 | 76.9 | | |

Problems Filling Maneuver Unit Orders, Class V
Table L-20

- The problems of unfilled orders have rippled into maneuver units. In the table below, supply type-maneuver unit combinations that have a zero BOH are presented. The table has been coded: 0 - time and distance problems; 1 - unsupported materiel; 2 - insufficient replenishment stockages; and 3 - unavailable transporters. Generally, once a unit experienced a zero BOH, the zero BOH continued to the end of the scenario.

- From table L-21 below, zero BOH are attributed to shortages of transporters, shortages of replenishments, and large time-distances between maneuver units and their supporting CSS unit. The reader is cautioned regarding the "0"; some maneuver units consume everything on-hand, and cannot be provided a supply type fast enough regardless of the speed of the CSS system.

| Supply Type | Maneuver Unit | TP | | | | | | | | | | | | | | | | # of TPs |
|-------------|---------------|----|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----------|
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
| ER-MLRS | B00A1M2 | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 |
| ER-MLRS | B00A2M2 | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 12 |
| ER-MLRS | B00C1M2 | | | 0 | 0 | 0 | 0 | 0 | | | | | | 0 | 0 | 0 | 0 | 9 |
| ER-MLRS | B00C2M2 | | | 0 | 0 | 0 | 0 | 0 | 0 | | | | | 0 | 0 | 0 | 0 | 11 |
| ER-MLRS | B00G2M2 | | | | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 | 0 | 12 |
| ER-MLRS | B00G3M2 | | | | 2 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 | 0 | 0 | 10 |
| M107 (CB) | B00E1T2 | | | | | | | | | | | | | | 0 | 0 | 0 | 3 |
| M107 (CB) | B00E2T2 | | | | | | | | | | | | | | | 0 | 0 | 2 |
| M107 (CB) | B00E3T2 | | | | | | | | | | | | | | | 0 | 0 | 2 |
| M107 (CB) | B00E4T2 | | | | | | | | | | | | | | 0 | 0 | 0 | 3 |
| M26 | B00A1M2 | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 10 |
| M26 | B00A2M2 | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | | | | | 8 |
| M26 | B00C1M2 | | | 0 | 0 | 0 | 0 | 0 | | | | 0 | 0 | 0 | 0 | 0 | | 10 |
| M26 | B00C2M2 | | 0 | 0 | 0 | 0 | | | 0 | | | 2 | 0 | 0 | 0 | 0 | | 10 |
| M26 | B00G2M2 | | | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | | | | | | 7 |
| M26 | B00G3M2 | | | | 0 | 0 | 0 | | | | | | | | | | | 3 |
| M26 | B300AM2 | | | | | | | | | | | | | | | | 0 | 1 |

| Supply Type | Maneuver Unit | TP | | | | | | | | | | | | | | | | | # of TPs |
|-------------|---------------|----|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----------|
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | | |
| M26 | B300BM2 | | | | | | | | | | | | | | | | 0 | 1 | |
| M449A1 | B00A3H2 | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | |
| M449A1 | B00A4H2 | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | |
| M449A1 | B00C3H2 | | 3 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | |
| M449A1 | B00E1T2 | | | | | | | | | | | | | | | 0 | 0 | 2 | |
| M449A1 | B00E2T2 | | | | | | | | | | | | | | | | 0 | 1 | |
| M449A1 | B00E3T2 | | | | | | | | | | | | | | | | 0 | 1 | |
| M449A1 | B00E4T2 | | | | | | | | | | | | | | | | 0 | 1 | |
| M449A1 | B00E5T2 | | | | | | | | | | | | | | | 0 | 0 | 2 | |
| M449A1 | B00E6T2 | | | | | | | | | | | | | | | 0 | 0 | 2 | |
| M449A1 | B3002H2 | | | | | | | | | | | | | | | 0 | 0 | 2 | |
| M483A1 | B00A3H2 | | | 3 | 0 | 3 | 3 | 3 | 3 | 0 | 0 | 0 | | | | | | 9 | |
| M483A1 | B00A4H2 | | | 0 | 0 | 3 | | 3 | | 3 | 3 | | 0 | 0 | 0 | | | 9 | |
| M483A1 | B00C3H2 | | 3 | 3 | 3 | 3 | 0 | 0 | 0 | | | | | 0 | | | | 8 | |
| M483A1 | B00E1T2 | | 0 | 0 | | | | | | | | | | | | 0 | 0 | 4 | |
| M483A1 | B00E2T2 | | 0 | 0 | | | | | | | | | | | | | | 2 | |
| M483A1 | B00E3T2 | | 0 | 0 | | | | | | | | | | | | | | 2 | |
| M549A1 | B00A3H2 | | | | | | | | | | | | | | 0 | 3 | 0 | 3 | |
| M549A1 | B00C3H2 | | | | | | | | | | | | | | | | 0 | 1 | |
| M549A1 | B00E1T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M549A1 | B00E2T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M549A1 | B00E3T2 | | | | | | | | | | | | | | 0 | 0 | 0 | 3 | |
| M549A1 | B00E4T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M549A1 | B00E5T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M549A1 | B00E6T2 | | | | | | | | | | | | 0 | 0 | 0 | 0 | 0 | 5 | |
| M795 | B00A3H2 | | | | | | | | 0 | 0 | | | | | | 0 | | 3 | |
| M795 | B00A4H2 | | | | | | | | | | 0 | | | | | 0 | 0 | 3 | |
| M795 | B00C3H2 | | | | | | | | | | | 0 | | 0 | | 0 | 0 | 4 | |
| M795 | B00E1T2 | | | | | | | | | | | | | | 0 | | 0 | 2 | |
| M795 | B00E2T2 | | | | | | | | | | | | | | | 0 | 0 | 2 | |
| M795 | B00E3T2 | | | | | | | | | | | | | | | 0 | 0 | 2 | |
| M795 | B00E4T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M795 | B00E5T2 | | | | | | | | | | | | 0 | 0 | 0 | 0 | 0 | 5 | |
| M795 | B00E6T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M864 | B00A3H2 | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | |
| M864 | B00A4H2 | | | 0 | 0 | 0 | 0 | 0 | 0 | 3 | | | | | | | | 7 | |
| M864 | B00C3H2 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | |
| M864 | B00E1T2 | | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | |
| M864 | B00E2T2 | | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | |
| M864 | B00E3T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M864 | B00E4T2 | | | | | | | | | | | | 0 | 0 | 0 | 0 | 0 | 5 | |

| Supply Type | Maneuver Unit | TP | | | | | | | | | | | | | | | | | # of TPs |
|-------------|---------------|----|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----------|
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | | |
| M864 | B00E5T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M864 | B00E6T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| M864 | B3003H2 | | | | | | | | | | | | | | | | 0 | 1 | |
| MSTAR | B00A1M2 | | | | 0 | 0 | 0 | 0 | 0 | 0 | | | | | | | | 6 | |
| MSTAR | B00A2M2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | | | | | | | 6 | |
| MSTAR | B00C1M2 | | | 0 | 0 | 0 | 0 | | | | | | | | | | | 4 | |
| MSTAR | B00C2M2 | | | 0 | 0 | 0 | | | | | | | | | | | | 3 | |
| MSTAR | B00G2M2 | | | | | 0 | 0 | 0 | 0 | | | | | | | | | 4 | |
| MSTAR | B00G3M2 | | | | | 0 | 0 | | | | | | | | | | | 2 | |
| XM898 | B00A3H2 | | | 3 | 0 | | | | | | | | | | | | | 2 | |
| XM898 | B00A4H2 | | | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | | | | | | | 8 | |
| XM898 | B00C3H2 | | 0 | 0 | 0 | 0 | | 0 | 0 | | | 0 | | 0 | 0 | 0 | 0 | 11 | |
| XM898 | B00E1T2 | | | | | | | | | | | | | 0 | 0 | 0 | 0 | 4 | |
| XM982 | B00A3H2 | | | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | | | 0 | | 0 | 9 | |
| XM982 | B00A4H2 | | | 3 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | | | | | | | 8 | |
| XM982 | B00C3H2 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | |
| XM982 | B00E1T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 10 | |
| XM982 | B00E2T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 11 | |
| XM982 | B00E3T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 11 | |
| XM982 | B00E4T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | 10 | |
| XM982 | B00E5T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 0 | 9 | |
| XM982 | B00E6T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | 10 | |
| XM982 | B00E7T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 9 | |
| XM982 | B00E8T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 9 | |
| XM982 | B00E9T2 | | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | | 9 | |
| XM982 | B3003H2 | | | | | | | | | | | | | | | | 0 | 1 | |

Causes for Zero BOH
Table L-21

To quantify a measure of risk, the maximum consumption of class V by a unit for any TP is compared with the current BOH for each TP; if the value is less than one, the unit would exhaust its supplies prior to repeating the activities of this "maximum" TP. Where "at risk" is less than one TP of supply, class V was generally provided to maneuver units without placing them "at risk". Twenty-eight maneuver units were "at risk." See Table L-22.

| MANEUVER UNIT | TP | | | | | | | | | | | | | | | | # of TPs |
|---------------|----|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----------|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
| B00A1M2 | | | 1 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 2 | 2 | 2 | 2 | 14 |
| B00A2M2 | | | 1 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 1 | 1 | 1 | 1 | 14 |
| B00A3H2 | | 3 | 7 | 7 | 7 | 7 | 6 | 6 | 6 | 6 | 6 | 7 | 7 | 8 | 8 | 7 | 15 |
| B00A4H2 | | 2 | 7 | 7 | 7 | 7 | 7 | 6 | 6 | 6 | 5 | 6 | 6 | 7 | 7 | 6 | 15 |
| B00C1M2 | | 3 | 3 | 3 | 3 | 3 | 3 | 2 | 2 | 2 | 1 | 1 | 2 | 3 | 3 | 3 | 15 |
| B00C2M2 | | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 2 | 2 | 1 | 2 | 2 | 2 | 2 | 15 |
| B00C3H2 | | 7 | 7 | 6 | 7 | 6 | 6 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 15 |
| B00E1T2 | 1 | 3 | 3 | 2 | 3 | 3 | 3 | 3 | 3 | 4 | 4 | 6 | 7 | 7 | 8 | 8 | 16 |
| B00E2T2 | 1 | 3 | 3 | 2 | 2 | 3 | 3 | 3 | 3 | 3 | 3 | 4 | 5 | 6 | 6 | 7 | 16 |
| B00E3T2 | 1 | 2 | 2 | 1 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 3 | 3 | 5 | 6 | 7 | 16 |
| B00E4T2 | 1 | 1 | 1 | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 4 | 6 | 7 | 8 | 15 |
| B00E5T2 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 3 | 4 | 5 | 6 | 6 | 16 |
| B00E6T2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 4 | 5 | 6 | 6 | 16 |
| B00E7T2 | | | | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 12 |
| B00E8T2 | | | | | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 12 |
| B00E9T2 | | | | | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 12 |
| B00G2M2 | | 1 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 2 | 2 | 2 | 15 |
| B00G3M2 | | 1 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | | 1 | 1 | 1 | 1 | 1 | 14 |
| B3001H2 | | | | | | | | | | | | 1 | 1 | 1 | 1 | 1 | 5 |
| B3002DC | | | | | | | | | | | | | | 1 | | | 1 |
| B3002H2 | | | | | | | | | | | | | | | 2 | 3 | 2 |
| B3003DC | | | | | | | | | | | | | 1 | 1 | 1 | 1 | 4 |
| B3003H2 | | | | | | | | | | | | | | | | 4 | 1 |
| B300AM2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 16 |
| B300BM2 | | | | | | | | | | | | | | 1 | 2 | 2 | 3 |
| B3021MX | | | | | | | | | | | | | | | 1 | 1 | 2 |
| B3022MX | | | | | | | | | | | | | | | 1 | 1 | 2 |
| B3031AR | | | | | | | | | | | | | | | | 1 | 1 |

"At Risk" Units, Class V Risk
Table L-22

(d) Observations.

- 1) There were several occurrences of zero balance on hand for the 155MM munition type; however, at no time were all 155MM sub-munition categories at zero balance.
- 2) For the MLRS munition type, the ER-MLRS sub-munition had a few occurrences of zero balance; however, at no time were all MLRS sub-munition categories at zero balance.
- 3) Most problems filling maneuver units orders for Class V were due to nonavailability of transporters; the primary cause for zero balance on hand for Class V was time and distance problems.

APPENDIX A

DDA VIC Name to Unit Name Cross Reference

| VIC Name | Unit Name |
|----------|-----------------------------------|
| B000CFC | CFC HQ |
| B00RCSB | CORPS REAR SPT BN |
| B02RCSB | CORPS REAR SPT BN |
| B000000 | III CORPS |
| B000PAT | 1ST PATRIOT BN HQ |
| B001PAT | A BTRY 1ST PATRIOT BN |
| B002PAT | B BTRY 1ST PATRIOT BN |
| B003PAT | C BTRY 1ST PATRIOT BN |
| B004PAT | D BTRY 1ST PATRIOT BN |
| B00FCSB | CORPS FWD SPT BN |
| B02FCSB | CORPS FWD SPT BN |
| B001CSA | III CORPS SUPPORT AREA |
| B001ASP | 501ST FASP-1 |
| B002ASP | 501ST FASP-2 |
| B003ASP | 501ST FASP-3 |
| B004ASP | 503RD FASP-1 |
| B005ASP | 503RD FASP-2 |
| B00A002 | 63TH FA BDE HQ III CORPS ARTY |
| B00A1M2 | 1ST BN 63TH FA BDE (MLRS) |
| B00A2M2 | 2ND BN 63TH FA BDE (MLRS) |
| B00A3H2 | 3RD BN 63TH FA BDE (155 SP) |
| B00A4H2 | 4th BN 63TH FA BDE (155 SP) |
| B00C002 | 65TH FA BDE HQ III CORPS ARTY |
| B00C1M2 | 1ST BN 65TH FA BDE (MLRS) |
| B00C2M2 | 2ND BN 65TH FA BDE (MLRS) |
| B00C3H2 | 3RD BN 65TH FA BDE (155 SP) |
| B00E002 | 67TH FA BDE HQ III CORPS ARTY |
| B00E1T2 | A BTRY 1ST BN 67TH FA BDE (155 T) |
| B00E2T2 | B BTRY 1ST BN 67TH FA BDE (155 T) |
| B00E3T2 | C BTRY 1ST BN 67TH FA BDE (155 T) |
| B00E4T2 | A BTRY 2ND BN 67TH FA BDE (155 T) |
| B00E5T2 | B BTRY 2ND BN 67TH FA BDE (155 T) |
| B00E6T2 | C BTRY 2ND BN 67TH FA BDE (155 T) |
| B00E7T2 | A BTRY 3RD BN 67TH FA BDE (155 T) |
| B00E8T2 | B BTRY 3RD BN 67TH FA BDE (155 T) |
| B00E9T2 | C BTRY 3RD BN 67TH FA BDE (155 T) |
| B00G002 | 69TH FA BDE HQ III CORPS ARTY |
| B00G1M2 | 1ST BN 69TH FA BDE (MLRS) |
| B00G2M2 | 2ND BN 69TH FA BDE (MLRS) |
| B00G3M2 | 3RD BN 69TH FA BDE (MLRS) |
| B00AVNB | 10TH AVN BDE III CORPS |
| B000GRP | 103RD AVN GROUP 10TH AVN BDE |
| B00A00H | 1ST BN 103RD AVN GRP |
| B00B00H | 2ND BN 103RD AVN GRP |
| B000RGT | 102ND ATK HEL RGT 10TH AVN BDE |
| B00E00H | 1ST BN 102ND ATK HEL RGT |
| B00F00H | 2ND BN 102ND ATK HEL RGT |

| VIC Name | Unit Name |
|----------|------------------------------|
| B00G00H | 3RD BN 102ND ATK HEL RGT |
| B3000MX | 3D INFANTRY DIVISION (MECH) |
| B300DSB | 3D DIVISION SUPPORT AREA |
| B3000DC | 3D CAV SQDN 3D ID |
| B3001DC | A TRP 3D CAV SQDN |
| B3002DC | B TRP 3D CAV SQDN |
| B3003DC | C TRP 3D CAV SQDN |
| B3000AD | 1ST CAV DIV AD BN |
| B300AAD | A CO, 3ID AD BN |
| B300BAD | B CO, 3ID AD BN |
| B300CAD | C CO, 3ID AD BN |
| B3010MX | 1ST BDE 3D ID |
| B3010RE | 1ST BDE RECON TRP |
| B3011MX | TF 1-77 MECH |
| B3011FC | FWD SPT CO |
| B3012MX | TF 1-80 MECH |
| B3012FC | FWD SPT CO |
| B3013AR | TF 1-2 AR |
| B3013FC | FWD SPT CO |
| B3001EN | 1ST BN, 3RD ENG REGT (3 COs) |
| B3002EN | 2ND BN, 3RD ENG REGT (3 COs) |
| B3004EN | 551ST EN BN (CORPS) |
| B301FSB | FSB 1ST BDE 3D ID |
| B301ATP | 1ST BDE 3ID AMMO TRANS PT |
| B3020MX | 2ND BDE 3D ID |
| B3020RE | 2ND BDE RECON TRP |
| B3021MX | TF 1-78 MECH |
| B3021FC | FWD SPT CO |
| B3022MX | TF 1-79 MECH |
| B3022FC | FWD SPT CO |
| B3023AR | TF 1-4 AR |
| B3023FC | FWD SPT CO |
| B3003EN | 3RD BN, 3RD ENG REGT (3 COs) |
| B302FSB | FSB 2ND BDE 3D ID |
| B302ATP | 2ND BDE 3ID AMMO TRANS PT |
| B3030AR | 3RD BDE 52RD ID |
| B3030RE | 3RD BDE RECON TRP |
| B3031AR | TF 1-3 AR |
| B3031FC | FWD SPT CO |
| B3032AR | TF 1-5 AR |
| B3032FC | FWD SPT CO |
| B3033MX | TF 1-81 MECH |
| B3033FC | FWD SPT CO |
| B303FSB | FSB 3RD BDE 3D ID |
| B303ATP | 3RD BDE 3ID AMMO TRANS PT |
| B300002 | 3D DIVISION ARTY |
| B3001H2 | 1ST BN 3D FA (155 SP) |
| B3002H2 | 2ND BN 3D FA (155 SP) |
| B3003H2 | 3RD BN 3D FA (155 SP) |

| VIC Name | Unit Name |
|----------|---------------------|
| B3000M2 | 3D FA (MLRS) |
| B300AM2 | A BTRY 3D FA (MLRS) |
| B300BM2 | B BTRY 3D FA (MLRS) |
| B30100H | 3D AVN BDE HQ |
| B3000LH | 3D CAV SQDN FARP |
| B30A00H | 1ST ATK BN 3D AVN |
| B30C00H | 3RD LIFT BN 3D AVN |

APPENDIX B

DEFINITIONS

Specific supply analysis definitions are listed below:

(1) Amount Authorized of this supply type: Amount of this supply type that this unit is authorized at the end of the TP, this number is calculated by multiplying the number of available systems that use this supply type by the amount authorized per system. This number can change from one TP to another due to weapon losses.

(2) Balance on-Hand of this supply type: Amount of this supply type that this unit has on hand at the end of the TP.

(3) Amount Used during this TP: Amount of this supply type that this unit used during this TP.

(4) Amount Lost during this TP: Amount of this supply type that this unit lost due to attrition of systems (when a system is damaged in combat a percentage (50%) of its on-board supplies are lost).

(5) Ratio of Balance on-Hand to Amount Authorized: A percent value used to indicate overall assessment of a munition; when this percent value is low, a greater risk is indicated as to possibility of exhausting all supplies.

(6) Total Amount Authorized during this TP: The sum of each amount authorized of each supply type at the end of the TP. The stockages are redistributed, consumed, or lost as the scenario proceeds. As units are engaged and attrited, the amount-authorized is reconciled with the number of surviving weapon systems.

(7) Total Amount on-Hand during this TP: The sum of the amount of each supply type that the units actually have in stock at the end of the TP. This amount is reduced by consumption, attrition, and other activities that may reduce the stockage of a supply type.

(8) Total Amount Used during this TP: The sum of the amount of each supply type consumed as a result of movement and combat at the end of the TP.

(9) Total Amount Lost during this TP: The sum of the amount of each supply type lost due to attrition of systems at the end of the TP (when a system is damaged in combat, a percentage of its on-board supplies are lost).

(10) Total Amount on-Order during this TP: The sum of the amounts of each supply ordered by each unit during a period. As materiel is consumed, units initiate orders based on a re-order threshold to restock its supplies. If an order cannot be shipped for reasons of shortages of stocks or movers, a unit will re-order the replenishments during the next period.

(11) Timely fashion: The manner in which a unit is supported when a negative consequence did not result. When a maneuver unit calls for replenishment of supplies, the support of the maneuver unit shall be said to be in a "timely fashion," if the maneuver unit did not suffer for lack of supplies. For class III, a unit suffers when it is forced to stop for lack of class III. For class V, a unit suffers a negative consequence when it exhausts a class V supply type.

(12) Risk: The proportion of TPs that each supply type for each unit can be expected to last given the greatest consumption for the scenario. The higher the measure, the greater the quantity of stockage, hence the lower the likelihood of not being able to repeat the highest consumption of a TP.

(13) Standard Resupply: Maneuver units will generate an order for a supply type when, per the resupply schedule, the on-hand plus on-order quantity is less than 75 percent of the authorized quantity. The magnitude of the order is the amount of each supply type to bring the on-hand plus on-order quantity up to the authorized quantity. Routinely, the order is for 25% of authorized. When the shipment arrives, the on-hand balance will increase, and the maneuver unit will issue an order when the on-hand quantity again falls below the 75% authorized. Exceptions to this resupply process occur when, for lack of trucks or stocks, an order cannot be filled or shipped. When the order (or portion of same) cannot be shipped in the period it was requested, the unfilled portion is lost - there are no backorders or due-outs. The maneuver unit will reassess its needs during the next period. Standard resupply can be divided into two types: supply point distribution (SPD) and unit distribution (UD). A unit that uses SPD provides its own organic transporters to convey replenishments between the supply unit(s) and itself; a unit using UD requires the supply unit to provide both replenishments and transporters.

(14) Emergency Resupply: Maneuver units will generate an "emergency" order for a supply type when, per the resupply schedule, the on-hand plus on-order quantity is less than 50 percent of the authorized quantity. The magnitude of the order is the amount of each supply type to bring the on-hand quantity up to 50% of the authorized quantity. When the shipment arrives, the on-hand balance will increase. This is "emergency resupply." Emergency resupply is subject to a number of factors: (1) the availability of replenishment stockages; (2) the availability of helicopter support to provide airlift between the supporting CSS unit(s) and the requesting maneuver unit; and (3) the hostile environment surrounding the maneuver unit. If the scenario is short-lived or has intensive combat, the last factor can be the most limiting. Helicopters will not provide lift to maneuver units that are under assault. If any one of the factors prohibits emergency resupply, the "emergency" request for replenishments will be routed for "standard" resupply. When the order (or portion of same) cannot be shipped in the time period it was requested, the unfilled portion is lost - there are no backorders or due-outs - the unit must wait for the next period per the resupply schedule to assess its stockage position and re-order.

APPENDIX C
FIGURES AND TABLES

| Unit Name | Amount Shipped | # of Deliveries | Minimum Time to Deliver | Avg Time to Deliver | Maximum Time to Deliver |
|-----------|----------------|-----------------|-------------------------|---------------------|-------------------------|
| B001CSA | 133,018.26 | 7 | 7.2 | 8.62 | 12.3 |
| B00RCSB | 25,251.4 | 40 | 1.1 | 1.33 | 1.53 |
| B02RCSB | 10,169.26 | 31 | 4.01 | 4.62 | 5.41 |
| B300DSB | 3,487.36 | 2 | 6.53 | 7.41 | 8.29 |
| B3013FC | 3,662.51 | 1 | 6.07 | 6.07 | 6.07 |
| B301FSB | 4,671.5 | 2 | 3.59 | 3.69 | 3.79 |
| B302FSB | 4,601.68 | 1 | 8.67 | 8.67 | 8.67 |
| B3033FC | 3,738.78 | 1 | 4.9 | 4.9 | 4.9 |
| B303FSB | 4,765.67 | 1 | 1.79 | 1.79 | 1.79 |

| Unit Name | Amount Shipped | # of Non-Deliveries | Minimum Time to Deliver | Avg Time to Deliver | Maximum Time to Deliver |
|-----------|----------------|---------------------|-------------------------|---------------------|-------------------------|
| B001CSA | 41,520.24 | 1 | 1 | 1 | 1 |
| B00RCSB | 1,068.73 | 2 | 0 | 0.5 | 1 |
| B02RCSB | 1,128.87 | 5 | 0.5 | 1.9 | 3.75 |
| B300DSB | 2,562.45 | 1 | 7 | 7 | 7 |
| B3023FC | 4,010.08 | 1 | 5 | 5 | 5 |
| B3031FC | 3,768.44 | 1 | 4 | 4 | 4 |
| B3032FC | 3,742.23 | 1 | 4 | 4 | 4 |

Order to Deliver, Class III
Table C-1

| Unit Name | Amount Shipped | # of Deliveries | Minimum Time to Deliver | Avg Time to Deliver | Maximum Time to Deliver |
|-----------|----------------|-----------------|-------------------------|---------------------|-------------------------|
| B001ASP | 69,546.05 | 174 | 8.81 | 20.84 | 41.14 |
| B001CSA | 133,018.26 | 7 | 7.2 | 8.62 | 12.3 |
| B003ASP | 250.52 | 7 | 4.94 | 6.19 | 7.33 |
| B00RCSB | 25,251.4 | 40 | 1.1 | 1.33 | 1.53 |
| B02RCSB | 10,169.26 | 31 | 4.01 | 4.62 | 5.41 |
| B300DSB | 3,487.36 | 2 | 6.53 | 7.41 | 8.29 |
| B3013FC | 3,662.51 | 1 | 6.07 | 6.07 | 6.07 |
| B301ATP | 455 | 2 | 1.47 | 4.19 | 6.92 |
| B001FSB | 4,732.36 | 2 | 3.59 | 3.69 | 3.79 |
| B302ATP | 481.59 | 1 | 0.85 | 0.85 | 0.85 |
| B302FSB | 4,601.68 | 1 | 8.67 | 8.67 | 8.67 |
| B3033FC | 3,738.78 | 1 | 4.9 | 4.9 | 4.9 |
| B303ATP | 30 | 1 | 2.6 | 2.6 | 2.6 |
| B303FSB | 4,765.67 | 1 | 1.79 | 1.79 | 1.79 |
| B002ASP | 1,072.33 | 17 | 1.49 | 5.7 | 8.74 |
| B004ASP | 7,110.71 | 63 | 3.38 | 5.88 | 8.55 |
| B005ASP | 53,718.65 | 8 | 2.99 | 3.16 | 3.18 |

| Unit Name | Amount Shipped | # of Non-Deliveries | Minimum Time to Deliver | Avg Time to Deliver | Maximum Time to Deliver |
|-----------|----------------|---------------------|-------------------------|---------------------|-------------------------|
| B001ASP | 7,671.25 | 64 | 0.25 | 10.1 | 23 |
| B002ASP | 23.14 | 1 | 8.03 | 8.03 | 8.03 |
| B003ASP | 213.88 | 4 | 4.16 | 7.16 | 8.25 |
| B004ASP | 582.23 | 2 | 3.52 | 5.56 | 7.6 |
| B301ATP | 246.92 | 2 | 1 | 5.5 | 10 |

Order to Deliver, Class V
Table C-2

| TP | USED GALS | LOST GALS | REQUIREMENT CONSUMED | AMOUNT RECEIVED BY AIR | AMOUNT RECEIVED BY TRUCK | AMOUNT REQUESTED | AMOUNT SHIPPED | % of ORDERED |
|-------|--------------|--------------|-------------------------|------------------------------|--------------------------------|---------------------|-------------------|--------------|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | --- |
| 1 | 47,407 | 896 | 48,303 | 0 | 0 | 0 | 0 | --- |
| 2 | 25,277 | 1,389 | 26,666 | 0 | 0 | 0 | 0 | --- |
| 3 | 19,402 | 305 | 19,707 | 0 | 0 | 0 | 0 | --- |
| 4 | 19,191 | 178 | 19,369 | 0 | 1,125 | 108,670 | 45,435 | 42 |
| 5 | 19,530 | 208 | 19,738 | 0 | 3,366 | 53,129 | 3,356 | 6 |
| 6 | 23,769 | 140 | 23,909 | 0 | 3,350 | 63,123 | 3,364 | 5 |
| 7 | 27,581 | 659 | 28,240 | 0 | 2,245 | 54,743 | 6,589 | 12 |
| 8 | 21,719 | 119 | 21,839 | 0 | 3,333 | 65,143 | 3,327 | 5 |
| 9 | 25,822 | 14 | 25,836 | 0 | 3,347 | 181,422 | 45,080 | 25 |
| 10 | 20,974 | 4 | 20,978 | 0 | 3,333 | 138,147 | 3,320 | 2 |
| 11 | 81,130 | 364 | 81,494 | 0 | 6,971 | 454,666 | 56,503 | 12 |
| 12 | 38,070 | 1,170 | 39,240 | 0 | 7,944 | 163,011 | 11,417 | 7 |
| 13 | 31,626 | 1,942 | 33,568 | 0 | 4,329 | 167,600 | 7,023 | 4 |
| 14 | 31,534 | 543 | 32,077 | 0 | 5,788 | 162,603 | 21,024 | 13 |
| 15 | 28,026 | 2,594 | 30,620 | 0 | 15,279 | 269,290 | 44,791 | 17 |
| TOTAL | 461,058 | 10,525 | 471,584 | 0 | 60,409 | 1,881,548 | 251,228 | 13 |

Consumption of Class III, Gallons
Table C-3

| TP | USED STONS | LOST STONS | REQUIREMENT CONSUMED | AMOUNT RECEIVED BY AIR | AMOUNT RECEIVED BY TRUCK | AMOUNT REQUESTED | AMOUNT SHIPPED | % of ORDERED |
|-------|---------------|---------------|-------------------------|------------------------------|--------------------------------|---------------------|-------------------|--------------|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | --- |
| 1 | 2,816 | 20 | 2,836 | 0 | 70 | 2,860 | 2,726 | 95 |
| 2 | 2,150 | 30 | 2,180 | 0 | 0 | 2,485 | 2,164 | 87 |
| 3 | 720 | 2 | 722 | 0 | 189 | 1,156 | 1,001 | 87 |
| 4 | 346 | 4 | 350 | 0 | 336 | 627 | 368 | 59 |
| 5 | 115 | 2 | 116 | 0 | 509 | 487 | 169 | 35 |
| 6 | 291 | 1 | 292 | 0 | 662 | 187 | 63 | 34 |
| 7 | 626 | 5 | 632 | 0 | 680 | 435 | 302 | 69 |
| 8 | 131 | 2 | 133 | 0 | 406 | 211 | 26 | 12 |
| 9 | 413 | 0 | 413 | 0 | 605 | 344 | 343 | 100 |
| 10 | 301 | 0 | 301 | 0 | 766 | 180 | 93 | 52 |
| 11 | 687 | 9 | 696 | 0 | 528 | 232 | 122 | 53 |
| 12 | 259 | 10 | 269 | 4 | 666 | 75 | 75 | 100 |
| 13 | 752 | 15 | 767 | 9 | 760 | 336 | 269 | 80 |
| 14 | 696 | 1 | 698 | 25 | 379 | 425 | 342 | 80 |
| 15 | 746 | 13 | 758 | 13 | 769 | 202 | 197 | 98 |
| TOTAL | 11,050 | 115 | 11,165 | 51 | 7,325 | 10,244 | 8,262 | 81 |

Consumption of Class V, STONS
Table C-4

| CLASS III & V, TRUCKLOADS BY TP | | | | | | | | | | | | | | | | | |
|---------------------------------|--------|---------|----------|-------|-------|--------|--------|--------|------|------|------|-------|-------|---------|-------|-------|-------|
| TP | ER-MRS | LONGROW | M107(CB) | M16B1 | M26 | M449A1 | M493A1 | M549A1 | M795 | M864 | M933 | MSTAR | POL-B | STINGER | XM898 | XM982 | TOTAL |
| 1 | 0.7 | | 12.9 | 11.9 | 49.8 | 0.0 | 2.3 | 16.7 | 3.9 | 7.7 | | 45.0 | | | 3.9 | 3.3 | 158.1 |
| 2 | 3.8 | 1.4 | 12.9 | 11.9 | 86.1 | 0.0 | 7.8 | 16.7 | 7.5 | 10.0 | | 101.7 | | 1.1 | 7.4 | 4.3 | 272.6 |
| 3 | 4.2 | 1.4 | 12.9 | 11.9 | 97.0 | 0.0 | 12.0 | 16.7 | 8.1 | 10.0 | | 137.3 | | 1.1 | 7.4 | 4.3 | 324.3 |
| 4 | 4.2 | 1.4 | 12.9 | 11.9 | 97.0 | 0.0 | 22.4 | 16.7 | 8.1 | 10.0 | | 148.1 | 19.6 | 1.1 | 7.4 | 5.2 | 366.0 |
| 5 | 4.2 | 1.4 | 12.9 | 11.9 | 97.0 | 0.0 | 33.9 | 16.7 | 8.1 | 10.7 | | 148.1 | 22.4 | 1.1 | 7.4 | 5.2 | 381.0 |
| 6 | 4.2 | 1.4 | 12.9 | 11.9 | 97.0 | 1.0 | 35.4 | 16.7 | 8.9 | 10.7 | | 148.1 | 25.2 | 1.1 | 8.8 | 5.2 | 388.5 |
| 7 | 4.2 | 1.4 | 18.7 | 11.9 | 107.6 | 1.0 | 35.9 | 16.7 | 8.9 | 10.7 | | 148.1 | 28.9 | 1.1 | 8.8 | 5.6 | 409.5 |
| 8 | 4.2 | 1.4 | 18.7 | 11.9 | 107.6 | 1.0 | 37.7 | 16.7 | 8.9 | 10.7 | | 148.1 | 31.6 | 1.1 | 8.8 | 5.6 | 414.0 |
| 9 | 4.2 | 1.4 | 18.7 | 11.9 | 122.2 | 1.0 | 37.7 | 16.7 | 10.4 | 10.7 | | 148.1 | 51.1 | 1.1 | 8.8 | 6.5 | 450.5 |
| 10 | 4.2 | 1.4 | 18.7 | 11.9 | 125.0 | 2.0 | 37.7 | 16.7 | 10.4 | 10.7 | | 148.1 | 51.1 | 1.1 | 8.8 | 7.2 | 455.0 |
| 11 | 4.2 | 1.4 | 18.7 | 11.9 | 125.0 | 2.0 | 41.4 | 18.9 | 10.7 | 10.7 | | 148.1 | 51.1 | 1.1 | 8.9 | 7.2 | 461.3 |
| 12 | 4.2 | 1.4 | 18.7 | 11.9 | 125.0 | 2.0 | 41.4 | 19.1 | 11.8 | 10.7 | 0.1 | 149.2 | 51.1 | 1.1 | 8.9 | 7.2 | 463.8 |
| 13 | 4.5 | 1.4 | 24.9 | 11.9 | 126.8 | 2.0 | 41.4 | 20.6 | 12.1 | 10.7 | 0.1 | 154.2 | 51.1 | 1.1 | 8.9 | 7.3 | 479.0 |
| 14 | 4.5 | 1.4 | 30.3 | 11.9 | 127.5 | 3.3 | 41.6 | 25.3 | 16.4 | 10.7 | 1.3 | 154.2 | 51.1 | 1.1 | 10.5 | 7.3 | 498.4 |
| 15 | 4.5 | 1.4 | 31.0 | 11.9 | 127.5 | 4.3 | 45.9 | 25.3 | 17.8 | 10.7 | 1.8 | 158.1 | 51.1 | 1.1 | 10.5 | 7.4 | 510.3 |

| CLASS III & V, PERCENTAGE BY TP | | | | | | | | | | | | | | | | | |
|---------------------------------|---------|---------|----------|--------|-------|--------|--------|--------|------|------|------|-------|-------|---------|-------|-------|-------|
| TP | ER-MLRS | LONGROW | M107(CB) | M116B1 | M26 | M419A1 | M433A1 | M549A1 | M795 | M864 | M933 | MSTAR | POL-B | STINGER | XM898 | XM982 | TOTAL |
| 1 | 0.44 | | 8.16 | 7.53 | 31.5 | 0 | 1.45 | 10.56 | 2.47 | 4.87 | | 28.46 | | | 2.47 | 2.09 | 100 |
| 2 | 1.39 | 0.51 | 4.73 | 4.37 | 31.58 | 0 | 2.86 | 6.13 | 2.75 | 3.67 | | 37.31 | | 0.4 | 2.71 | 1.58 | 100 |
| 3 | 1.3 | 0.43 | 3.98 | 3.67 | 29.91 | 0 | 3.7 | 5.15 | 2.5 | 3.08 | | 42.34 | | 0.34 | 2.28 | 1.33 | 100 |
| 4 | 1.15 | 0.38 | 3.52 | 3.25 | 26.5 | 0 | 6.12 | 4.56 | 2.21 | 2.73 | | 40.46 | 5.36 | 0.3 | 2.02 | 1.42 | 100 |
| 5 | 1.1 | 0.37 | 3.39 | 3.12 | 25.46 | 0 | 8.9 | 4.38 | 2.13 | 2.81 | | 38.87 | 5.88 | 0.29 | 1.94 | 1.36 | 100 |
| 6 | 1.08 | 0.36 | 3.32 | 3.06 | 24.97 | 0.26 | 9.11 | 4.3 | 2.29 | 2.75 | | 38.12 | 6.49 | 0.28 | 2.27 | 1.34 | 100 |
| 7 | 1.03 | 0.34 | 4.57 | 2.91 | 26.28 | 0.24 | 8.77 | 4.08 | 2.17 | 2.61 | | 36.17 | 7.06 | 0.27 | 2.15 | 1.37 | 100 |
| 8 | 1.01 | 0.34 | 4.52 | 2.87 | 25.99 | 0.24 | 9.11 | 4.03 | 2.15 | 2.58 | | 35.77 | 7.63 | 0.27 | 2.13 | 1.35 | 100 |
| 9 | 0.93 | 0.31 | 4.15 | 2.64 | 27.13 | 0.22 | 8.37 | 3.71 | 2.31 | 2.38 | | 32.87 | 11.34 | 0.24 | 1.95 | 1.44 | 100 |
| 10 | 0.92 | 0.31 | 4.11 | 2.62 | 27.47 | 0.44 | 8.29 | 3.67 | 2.29 | 2.35 | | 32.55 | 11.23 | 0.24 | 1.93 | 1.58 | 100 |
| 11 | 0.91 | 0.3 | 4.05 | 2.58 | 27.1 | 0.43 | 8.97 | 4.1 | 2.32 | 2.32 | | 32.1 | 11.08 | 0.24 | 1.93 | 1.56 | 100 |
| 12 | 0.91 | 0.3 | 4.03 | 2.57 | 26.95 | 0.43 | 8.93 | 4.12 | 2.54 | 2.31 | 0.02 | 32.17 | 11.02 | 0.24 | 1.92 | 1.55 | 100 |
| 13 | 0.94 | 0.29 | 5.2 | 2.48 | 26.47 | 0.42 | 8.64 | 4.3 | 2.53 | 2.23 | 0.02 | 32.19 | 10.67 | 0.23 | 1.86 | 1.52 | 100 |
| 14 | 0.9 | 0.28 | 6.08 | 2.39 | 25.58 | 0.66 | 8.35 | 5.08 | 3.29 | 2.15 | 0.26 | 30.94 | 10.25 | 0.22 | 2.11 | 1.46 | 100 |
| 15 | 0.88 | 0.27 | 6.07 | 2.33 | 24.99 | 0.84 | 8.99 | 4.96 | 3.49 | 2.1 | 0.35 | 30.98 | 10.01 | 0.22 | 2.06 | 1.45 | 100 |

Truckloads On-Road, CSS-to-Maneuver Units
Table C-5

| | | CLASS III, AMOUNT ON-HAND BY HOUR | | | | | | | | | | | | | | | | | | | |
|----|-----------|-----------------------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--|--|--|--|
| | B001CSA | B00FCSB | B00RCSE | B02FCSE | B02RCSE | B300DSB | B3011FC | B3012FC | B3013FC | B301FSB | B3021FC | B3022FC | B3023FC | B302FSB | B3031FC | B3032FC | B3033FC | | | | |
| 0 | 2,412,500 | 480,000 | 575,000 | 480,000 | 575,000 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 4 | 2,412,500 | 480,000 | 575,000 | 480,000 | 575,000 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 8 | 2,412,497 | 480,000 | 575,000 | 480,000 | 575,000 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 12 | 2,412,032 | 480,000 | 575,000 | 480,000 | 575,000 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 16 | 2,370,364 | 480,000 | 572,754 | 480,000 | 573,875 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 20 | 2,370,039 | 480,000 | 570,518 | 480,000 | 572,755 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 24 | 2,353,119 | 463,197 | 568,293 | 480,000 | 571,616 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 28 | 2,353,396 | 475,487 | 566,074 | 480,000 | 571,593 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 32 | 2,353,520 | 475,487 | 563,860 | 480,000 | 570,480 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 36 | 2,311,193 | 475,487 | 561,653 | 480,000 | 569,346 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 40 | 2,290,580 | 454,803 | 559,462 | 480,000 | 568,217 | 428,600 | 12,500 | 12,500 | 22,500 | 125,000 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 44 | 2,254,446 | 466,969 | 557,287 | 480,000 | 568,195 | 428,600 | 12,500 | 12,500 | 22,500 | 120,329 | 12,500 | 12,500 | 22,500 | 125,000 | 22,500 | 22,500 | 12,500 | | | | |
| 48 | 2,254,502 | 466,969 | 555,127 | 480,000 | 567,089 | 425,113 | 12,500 | 12,500 | 22,500 | 120,268 | 12,500 | 12,500 | 22,500 | 120,398 | 22,500 | 22,500 | 12,500 | | | | |
| 52 | 2,254,417 | 466,969 | 552,971 | 480,000 | 565,960 | 425,113 | 12,500 | 12,500 | 22,500 | 120,004 | 12,500 | 12,500 | 22,500 | 120,398 | 22,500 | 22,500 | 8,761 | | | | |
| 56 | 2,254,472 | 466,969 | 550,822 | 480,000 | 564,831 | 422,550 | 12,500 | 12,500 | 18,838 | 120,004 | 12,500 | 12,500 | 18,490 | 120,398 | 18,732 | 18,758 | 8,761 | | | | |
| 60 | 2,212,389 | 466,969 | 548,680 | 480,000 | 563,702 | 422,550 | 12,500 | 12,500 | 18,838 | 120,004 | 12,500 | 12,500 | 18,490 | 120,398 | 18,732 | 18,758 | 8,761 | | | | |

Class III Balance for Supply Points, CSS-to Maneuver Units
Table C-6